

# IEEE / NERC Ultra Max Plus Battery Testing Kit

Model # Ultra Max Plus-Kit



Complete Ultra-Max-Plus Kit

### **Product Overview**

The Ultra-Max Plus Kit is the complete solution for testing per IEEE and NERC standards. The Ultra-Max Plus Kit has three parts: an IBEX-Ultra Portable Ohmic Battery Tester, SG-Ultra Max Digital Hydrometer, and Exmons Ultra+ All-in-One Management Software.

The Ultra-Max Plus Kit tests internal resistance, voltage, connection resistance, temperature, DC current, ripple current, specific gravity (state of charge), and electrolyte temperature. Eagle Eye's IEEE/NERC Kits are completely customized to meet your specific battery testing requirements. Let us know your specific applications, testing requirements and budget, and we can tailor a battery testing kit to fit your needs.

#### **Features**

- Complete Battery Testing Kit meets IEEE/NERC Requirements for battery maintenance
- Measures: Internal Resistance, Voltage, Inter-Cell Resistance, Temperature, DC Current, Ripple Current, Specific Gravity and Electrolyte Temperature
- Store up to 4,800 results with IBEX-Ultra and 1,024 with SG-
- Exmons Ultra+ Software included for All-in-One battery management
- Measures and Stores Results in 3-4 seconds

# **Technical Specifications**

Battery Capacity Range: 5 – 6000 Ah

Voltage & I.R. Range: 0 – 60 VDC / I.R. – 50 VDC

Internal Storage: 600 or 4800 Test Results, 4 or 80

**Battery Models** 

Resolution:

Voltage: 10 mV **IBEX-Ultra Key Specs:** 

Resistance: 0.001 m $\Omega$ 

Temperature: 0.5 C (0.5 °F)

Accuracy:

DC Voltage: ±0.5%

Internal Resistance: ±0.5%

Temperature: ±2.0%

# Measurement Range:

Density: 0.000 - 3.000 g/cm3

Sample Temperature: \*0 - 80 °C (32 - 176 °F)

Viscosity: 0 - 1,000 mPa

Internal Memory: 1024 Results SG-Ultra Max Key Specs: Resolution: 0.0001 g/cm3

Accuracy:

Density: 0.001 g/cm3

Temperature: ±0.2 °C (±0.4 °F)

**Operating Environment:**  $10 - 50 \, ^{\circ}\text{C} \, (-15 - 122 \, ^{\circ}\text{F})$ 

### **IEEE / NERC Requirements**

- Meets IEEE Standards: 450-2010, 1188-2005, 1106-2005
- **NERC Compliance:** PRC-005-2



## Kit Includes

- IBEX-Ultra Kit
- SG-Ultra Max Kit
- Exmons Ultra Plus Management Software

# **Ordering Information**

No.	Model #	Description
1	Ultra-Max-Plus Kit	IBEX-Ultra Battery Tester, SG-Ultra Max Digital Hydrometer, Exmons Ultra Plus Software