

## LB-60-100 AC Load Bank



**LB-60-100 AC Load Bank**

### Product Overview

The **LB-60-100** Load Bank is designed to provide a temporary load for field servicing and testing 480VAC and 208VAC three phase 60HZ generators and inverters. The LB-60-100 load bank is air cooled. A 120VAC outlet is required to operate the fans and relays. The load is 100KW at 480VAC and 80KW at 208VAC. The unit will also test 120VAC & 240 VAC single phase.

Eagle Eye's AC Load Banks are among the smallest AC load banks in the industry that offer unmatched capacities with rugged durability. Each load bank is fully self-contained and designed for portable AC load testing that can easily withstand harsh testing environments. Straightforward individual fan switches, load step switches, and master load switches make the unit user-friendly. Safety features are equipped on every AC Load Bank for fast acting, branch circuit fuse protection and sensors to prevent overheating and current overload.

### Product Features

- Portable, lightweight, and durable
- Temperature sensor removes load when over-temperature is detected
- Easy-to-use switches & controls for fan, load steps & master load
- Low-noise, high velocity cooling system
- Power indicator lights
- Quick connect for cables



**Padded Carrying Case**



**Load Cables**

### Technical Specifications

<b>Load Steps:</b>	12.5, 12.5, 25, 25, 25 KW on three phase 480VAC 10, 10, 20, 20, 20 KW on three phase 208VAC 6.5, 6.5, 13, 13, 13 KW on single phase 240VAC 1.6, 1.6, 3.2, 3.2, 3.2 KW on single phase 120VAC
<b>Meters:</b>	0-600V voltmeter 0-250A ammeter 55-65HZ frequency meter
<b>Cooling:</b>	Forced air cooling
<b>Dimensions:</b>	56 x 20 x 53 cm (22 x 8 x 21 in)
<b>Weight:</b>	27 kg (60 lbs)

### Kit Includes

- LB-60-100 Load Bank
- Portable Carrying Case
- 10' Cables
- User Manual

### Ordering Information

No.	Model #	Description
1	LB-60-100	60HZ 480/208 3PHASE 100KW AT 480VAC AND 80KW AT 208VAC