

LB-60-30 AC Load Bank



LB-60-30 AC Load Bank

Product Overview

The **LB-60-30** Load Bank is designed to provide a temporary load for field servicing and testing 120/240 volt single phase or 120/208 three phase 60HZ generators and inverters. The LB-60-30 load bank is air cooled and completely self contained. It has a 30KW 3 phase and a 20KW single phase load.

Eagle Eye's AC Load Banks are among the smallest AC load banks in the industry that offer unmatched capacities with rugged durability. Each load bank is fully self-contained and designed for portable AC load testing that can easily withstand harsh testing environments. Straightforward individual fan switches, load step switches, and master load switches make the unit user-friendly. Safety features are equipped on every AC Load Bank for fast acting, branch circuit fuse protection and sensors to prevent overheating and current overload.

Product Features

- Portable, lightweight, and durable
- Temperature sensor removes load when over-temperature is detected
- Easy-to-use switches & controls for fan, load steps & master load
- Low-noise, high velocity cooling system
- Power indicator lights
- Quick connect for cables



Load Cables



Padded Carrying Case

Technical Specifications

Load Steps:	120VAC Single Phase: .33, .66, .66, 1.66, 3.33, 3.33 KW 240VAC Single Phase: .66, 1.33, 1.33, 3.33, 6.66, 6.66 KW 208VAC Three Phase: 1, 2, 2, 5, 10, 10 KW
Meters:	0-150V voltmeter 0-100A ammeter 55-65HZ frequency meter
Cooling:	Forced air cooling
Dimensions:	56 x 20 x 28 cm (22 x 8 x 11 in)
Weight:	18 kg (35 lbs)

Kit Includes

- LB-60-30 Load Bank
- Portable Carrying Case
- 10' Cables
- User Manual

Ordering Information

No.	Model #	Description
1	LB-60-30	60HZ 120/240VAC SINGLE PHASE 208V 3PHASE 30KW