




Projectors... and More!

LC-WAU200

3,000 ANSI Lumens / WXGA / 3LCD
"Short-Throw" Series Projector

LC-WAU200

3,000 ANSI lumens bright with 80% uniformity and a 3000:1 contrast ratio. Native WXGA resolution. Compatible with inputs up-to UXGA and WUXGA. Supports analog and digital video input in all color standards up-to 1080p. HDMI Digital connectivity with HDCP compliance. Short throw, with manual focus. Fixed image offset. Automatic vertical digital keystone correction. Accepts composite, component, and S-Video in all major standards. Displays both 4:3 and 16:9 aspect ratios. Supports most HDTV resolutions. Built-in 7 Watt sound system. Closed Caption decoding (NTSC). Wired network control. Side-accessed air filter & top accessed lamp for ease of maintenance. Color board modes. Custom warm-up screen. Auto input selection. Built-in Test Patterns. Security bar. Kensington® MicroSaver® security slot. PIN lock. 3 year projector warranty.



Included Accessories:

Quick Start Guide, Owner's Manual on CD-ROM, VGA Computer Input Cable (Dsub15 to Dsub15), 6.0 ft (1.8 m) Detachable Power Cord, Remote Control (with 2 AAA Batteries)

Optional Accessories:

Replacement Lamp, Ceiling Mount, Ceiling Post and Plate, Soft Carry Bag

Specifications: Model LC-WAU200

Brightness	3,000 ANSI Lumens	Image Signal Inputs	
Contrast Ratio	3000:1	Computer 1	Dsub15 x 1
Illumination Uniformity	80%	Computer 2 (switchable Monitor Out)	Dsub15 x 1
Resolution and Aspect Ratio	WXGA (1280x800), 16:10	Digital Video (w/ HDCP)	HDMI x 1
Color Reproduction	24-bit (16.7 million colors)	S-Video	S-Video x 1
Projection Lamp	230Watts UHP	Component Video	RCA x 3
Estimated Lamp Life (Normal / Eco)	3,000 / 5,000 hours	Composite Video	RCA x 1 (Shared with Component)
Total Pixels	3,072,000 (1280x800) x 3	Audio Signal Inputs	
Imaging System	0.59 in (15 mm) inorganic LCD Panels x 3	Computer Audio	MiniStereo x 1
Scanning Frequency	Auto: H Sync. 15-100 kHz, V Sync. 48-85 Hz	Video Audio	RCA x 2 (L/R)
Pixel Clock	up-to 150 MHz	Outputs	
Lens	Attached - Fixed Zoom and Manual Focus	Computer Monitor (Computer 2)	Dsub15 x 1
Lens Specs	Speed: f: 1.8; FL: 0.239 in (6.08 mm)	Audio Output	Variable, Stereo: MiniStereo x 1 Mono: 7 Watt
Lens Ratios	Throw:Width 0.46:1	Amplifier	
Image Diagonal	50-100 in (127-254 cm)	Speaker	1.4 in (3.7 cm) x 1 (Mono) as low as 34 dBA
Image Width	2.6-20 ft (0.79-6.1 m)	Fan Noise	
Throw Distance	1.57-3.28 ft (0.48-1.0 m)	Cabinet Size (HxWxD) - excluding legs	5.4 x 15.4 x 12.9 in (13.7 x 39.1 x 32.7 cm)
Projector Elevation Adjustment (legs)	up-to 10°	Weight	8.8 lb (4.0 kg)
Maximum Pitch	Up-to 30° Up or Down	Packaged Cabinet Size (HxWxD)	6.7 x 17.0 x 14.2 in (17.0 x 43.1 x 36.0 cm)
Anti Keystone	Fixed Image Offset, Ratio (Top/Bottom) 7.25:-1	Packaged Weight	9.48 lb (4.3 kg)
Vertical Keystone Correction	Digital: up-to 15° Up or Down	Operating Temperature	41-95°F (5-35°C)
Image Orientation	Normal, Reversed, Inverted	Electrical Safety Compliance	IEC / UL / cUL
Local Control / Power Management	Full Function / Auto Shutdown	Electromagnetic Compatibility	FCC Class B, CE Mark
Remote Control	Wireless x 1	Power Requirements	100-240V AC, 50/60 Hz
RS-232 Control	Dsub9 x 1	Power Consumption	0.5 W in Eco Standby mode, up-to 290 W
LAN Port	RJ45 x 1	Heat	up-to 990 BTU/hr
Computer Input in Pixels	up-to 1600x1200 (4:3), 1920x1200 (16:10)	Security Facilities	Kensington® Security Slot
Analog 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	UPC	4571194677089
Analog Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA	User Maintenance	Clean Filter, Replace Lamp
Digital 4x3 Inputs	UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC	Limited Warranty: to the original end use customer only	
Digital Wide Inputs	WUXGA, WSXGA+, WXGA+, WXGA	Projector	*3 years / 6000 hours
Video Formats	NTSC / PAL / SECAM	Lamp	*1 year ownership / 500 hours use (*whichever occurs first)
Video Input Analog	480i/p, 576i/p		
Video Input Digital	480p, 575p, 720p, 1080i/p		
Image Signal Resizing	Smart Scaling Technology		



205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com