

## LENSES FOR EK-850LU, EK-1000LU, EK-1100LU

14-Jun-21

## Screen Dimensions.

Resolution: WUXGA (1920x1200)

Aspect Ratio: (16:10)

H	2.7	3.1	3.8	4.4	5.0	6.2	7.5	8.8	10.0	11.3	13.3
W'	4.3	5.0	6.0	7.1	8.0	10.0	12.0	14.2	16.0	18.0	21.2
D"	60	70	85	100	113	141	170	200	226	255	300

Factory Specifications					Measurements and Calculations											
EIKI Part No.	Diagonal	Shift Range	T/W Throw (Distance to Screen) in feet.													
AH-EC22030	Min: 50"	V: -10% ~ +50%	Power Zoom and Focus	0.79	3.4	3.9	4.7	5.6	6.3	7.9	9.5	11.2	12.7	14.2	16.8	
	Max: 500"	H: +/- 20%	1.4x Zoom	1.11	4.7	5.5	6.7	7.9	8.9	11.1	13.4	15.8	17.8	20.1	23.6	
AH-EC21020	Min: 50"	V: -10% ~ +50%	Power Zoom and Focus	1.30	5.5	6.4	7.8	9.2	10.4	13.0	15.6	18.4	20.8	23.4	27.5	
	Max: 500"	H: +/- 20%	2.3x Zoom	3.02	12.8	14.9	18.1	21.4	24.1	30.2	36.2	42.7	48.3	54.3	64.0	
AH-EC21030	Min: 40"	V: -10% ~ +50%	Manual Zoom and Focus	1.46	6.2	7.2	8.7	10.3	11.7	14.6	17.5	20.6	23.3	26.2	30.9	
	Max: 500"	H: +/- 30%	2.0x Zoom	2.95	12.5	14.6	17.7	20.9	23.6	29.5	35.4	41.7	47.2	53.1	62.5	
AH-EC24010	Min: 50"	V: -10% ~ +50%	Power Zoom and Focus	2.99	12.7	14.8	17.9	21.2	23.9	29.9	35.8	42.3	47.8	53.7	63.3	
	Max: 500"	H: +/- 20%	2.0x Zoom	5.93	25.2	29.3	35.6	42.1	47.4	59.3	71.1	83.8	94.8	106.7	126	
				•			•	•		•				•		
AH-EC23030	Min: 60"	V: -10% ~ +50%	Manual Zoom and Focus	4.59	19.5	22.7	27.6	32.6	36.8	45.9	55.1	65.0	73.5	82.7	97.4	
	Max: 500"	H: +/- 30%	1.52x Zoom	7.02	29.8	34.8	42.1	49.9	56.2	70.2	84.3	99.4	112.4	126.4	149	

How to use the Throw Ratio (T/W) column. If your screen size does not appear on this chart, use the T/W column to find the lens you need.

Divide the Throw distance by the screen Width to get your "target T/W number". Then, look for a lens with a T/W range that covers it.

**These tables are a simulation.** They are the result of averaging and rounding. Lens performance is actually not linear, and non-mathematical: variations in behavior do occur.

Calculations are from the front glass of the lens and accurate to approximately +/- 3%. Specifications are subject to change without notice.

Eiki International, Inc. Tel: 800-242-3454, E-mail: usa@eiki.com

Website: http://www.eiki.com