

HQView500S

Universal HQV™ Scaler–Switcher-Scan Converter
with 3G-SDI In/Out & Genlock



Harnessing the power of the Reon™ video processor running state of the art HQV™ algorithms with expertly designed hardware and firmware from Calibre, HQView500S is a highly flexible image scaler and scan converter which provides stunning image quality for professional, broadcast and corporate AV users.

HQView500S provides 3G-SDI input and out connectivity with backwards compatibility with HD-SDI and SD-SDI. A Genlock input is provided for studio/staging use which can accept bi-level or tri-level sync or black & burst.

- Best in class professional image processing in a compact affordable 1U format
- Use as a routing switcher and universal interface for 3G-SDI, HD-SDI, DVI or HDMI switching and distribution systems, projectors and displays
- Improve video image quality with better detail and clarity
- Superior de-interlacing reduces image flicker and artefacts
- Remove picture noise from poor quality video sources
- Genlock and I/O Lock for in-camera use

- 3G-SDI, HDMI, DVI, VGA Analog, Component YPbPr, RGB/RGBS, Composite & S-Video inputs with signal compatibility up to 1080p & WUXGA
- 3G-SDI, HDMI/DVI & VGA Analog outputs
- PIP (Picture in Picture), POP (Picture on Picture), PAP (Picture alongside Picture)
- Motion adaptive per pixel video de-interlacing, HD & SD
- Multi-directional diagonal de-interlace filter
- Automatic 3:2 & 2:2 pull-down detection with automatic film, video and video over film detection
- Chroma and Luma transient improvement
- Edge anti-aliasing
- 4-field full resolution SD & HD processing
- 4D Motion Noise Adaptive HQV noise reduction for spatial and temporal noise
- Codec noise reduction for mosquito and block compression noise
- Direct input selection keys allow input selection without using menu system
- Flexible color calibration controls
- Gamma controls
- 10-bit signal inputs, 12-bit accurate internal processing
- Selectable processing versus latency: best picture and low latency modes
- Latency as low as 0.25-frame progressive inputs, 1.25-frames interlaced inputs
- I/O Lock, Genlock/Frame Sync and Free Run selectable output modes
- Flicker filter for interlaced output modes
- USB port for in-field firmware updates
- Programmable customer logo on menu
- TCP/IP remote control and Web Server
- Easy to navigate self-explanatory OSD menus

Calibre UK Ltd,
Cornwall House, Cornwall Terrace,
Bradford,
West Yorkshire
BD8 7JS

Europe: proavsales@calibreuk.com
+44 1274 394125
USA: usasales@calibreuk.com
Web: www.calibreuk.com

HQView500S

Universal HQV™ Scaler–Switcher-Scan Converter with 3G-SDI In/Out & Genlock

Inputs

2x Composite Video CVBS (NTSC, PAL & SECAM),
1x via BNC jack and 1x via Cinch/RCA
1x YC/S-Video via 4 pin mini DIN
1x Component analog video YPbPr(S) or RGB/RGBS
via 3 or 4 x BNC jack
1x HDMI with HDCP, 8/10/12 bit video compatible, 10-bit internal
processing depth. Audio strip-off of SPDIF compatible formats
1x DVI with HDCP
1x VGA Analog via 15HDD
1 x 3G-SDI, accepts 3G, HD and SD SDI signals via BNC,
supports 4:2:2 and 4:4:4 formats with audio de-embed

1x Genlock (V-Lock) input via BNC, accepts bi-level, tri-level sync
or black & burst, 50/59.94/60Hz formats

Supported video formats

HD 720p, 1080i, 1080psf (psf digital only), 1080p23.97/24/25/30,
1080p30, 1080p50, 1080p59.94, 1080p60
ED 480p, 576p (not via SDI)
SD 625i (576i), 525i (480i)
Common VESA graphics formats from 640x480 to 1920x1200
(with reduced blanking for 1920x1200 and 1600x1200 modes)

Multi standard support for CVBS & YC in PAL, NTSC, SECAM
formats with selectable 3D comb for composite

Outputs

1x 3G-SDI
1x DVI/HDMI with HDCP
(HDMI with deep color 8/10/12 bit support, via DVI connector)
1x VGA Analog via 15HDD
1x S/PDIF digital audio via RCA
*NB: 3G-SDI and VGA Analog outputs are disabled with HDCP-encrypted
input. Not all outputs are available simultaneously*

Supported Output formats:

DVI/VGA in common VESA formats 640x480 to 1920x1200, 720p, 1080p
3G-SDI in SMPTE formats 480i, 576i, 720p, 1080i, 1080p with selectable
audio embed
Selectable Genlock (V-Lock), I/O lock or frame rate conversion mode
Selectable aspect ratio conversion
Selectable vertical temporal filter for flicker reduction of interlaced outputs
(edge blend not available in this mode)

User Controls

Remote control via RS232, TCP/IP API and Web Server.
Keypad for direct input selection and control of common adjustments as well
as OSD menu access.
USB port for uploading software updates and new features

Power Requirements

100-264VAC, 35W typical

Warranty 3-years return to base warranty covers parts and labor, shipping
excluded.

HQView model >	100S	210	310	320	325	400S	420	500S	520	530
Front LCD menu or OSD control	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD	OSD	LCD
DVI/HDMI Inputs			X	X	X	X	X	X	X	X
Component Input			X	X		X	X	X	X	X
Composite/S-Video Inputs	X					X	X	X	X	X
VGA Analog Input			X	X		X	X	X	X	X
HD-SDI Input						X	X			
3G-SDI Input		X						X	X	X
DVI/HDMI Output	X	X	X	X	X	X	X	X	X	X
VGA Analog Output						X	X	X	X	X
3G-SDI Output								X	X	X
3G-SDI Audio embed/de-embed								X	X	X
HQV Processing	X	X	X	X	X	X	X	X	X	X
PIP/POP/PAP						X	X	X	X	X
TCP/IP Control	X	X	X	X	X	X	X	X	X	X
Low Latency Mode	X	X	X	X	X	X	X	X	X	X
Flicker Filter for Interlaced Output Modes								X	X	X
Geometry Correction, 4-Corner, Rotate		X	X	X	X		X		X	X
Genlock (V-Lock)								X	X	X
Pan, Zoom, Tilt	X	X	X	X	X	X	X	X	X	X
Edge Blending			X	X	X		X		X	X
Auto pan/zoom/tilt of content for blending			X	X	X		X		X	X
Projection Mapping/Warp				X	X		X		X	X



Calibre UK Ltd,
Cornwall House, Cornwall Terrace,
Bradford,
West Yorkshire
BD8 7JS

Europe: proavsales@calibreuk.com
+44 1274 394125
USA: usasales@calibreuk.com
Web: www.calibreuk.com