

409B-AEROSOL

ELECTROSOLVETM CONTACT CLEANER Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: Electrosolve[™] Contact Cleaner
SDS Code: 409B-Aerosol
Related Part # 409B-140G, 409B-340G

Recommended Use and Restriction on Use

Use: Zero-residue contact cleaner

Uses Advised Against: Do not use on live circuits or in presence of iginition source

Details of Manufacturer or Importer

Manufacturer MG Chemicals 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA

MG Chemicals (Head Office) 9347-193 Street Surrey, British Columbia V4N 4E7 CANADA

***** +1-800-340-0772
 Fax +1-800-340-0773
 E-MAIL <u>support@mgchemicals.com</u>

 WEB

 www.mgchemicals.com

 Image: mail of the system
 +1-905-331-1396

 Fax
 +1-905-331-2682

 E-MAIL
 info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY—leaks, spills, fires, exposures or accidents USA or CANADA: Call CHEMTREC **☎**: **+1-800-424-9300**

For emergencies involving dangerous goods; Collect 24/7 CANADA: Call CANUTEC ☎: +1-613-996-6666 or *666 on cellular phones



409B-AEROSOL

Section 2: Hazard(s) Identification

Classification of Hazardous Chemical

GHS Categories

Criteria		Category	Signal Word	Pictograms
Aspiration hazard		1	Danger	Health
Reproductive Toxicity		2	Warning	Health
Flammable Aerosol		2	Warning	Flame
Gas under pressure		Liquefied gas	Warning	Gas cylinder
Skin irritation		2	Warning	Exclamation
Specific Target Organ Toxicity	Single Exposure	3	Warning	Exclamation
Environmental Hazard	Chronic Aqua. Tox.	3	none	none

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H304: May be fatal if swallowed and enters airways
	H361: Suspected of damaging fertility or the unborn child
	H223: Flammable aerosol
	H280: Contains gas under pressure: may explode if heated

Section continued on the next page

Page **2** of **17** Date of Revision:08 February 2016 / Ver. 2.01



409B-AEROSOL

Pictograms	Hazard Statements	
$\mathbf{\wedge}$	H315: Causes skin irritation	
	H336: May cause drowsiness and dizziness	
•		
	H412: Harmful to aquatic life with long lasting effects	
No symbol mandated		
mandated		
Prevention	Precautionary Statements	
P102	Keep out of reach of children.	
P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood	
P261	Avoid breathing mist/vapors/spray.	
P271	Use only outdoors or in a well-ventilated area.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P280	Wear protective gloves/protective clothing/eye protection.	
P264	Wash hands thoroughly after handling.	
P273	Avoid release to the environment.	
Response	Precautionary Statements	
P308 + P313	IF exposed or concerned: Get medical advice/attention.	
P301 + P310, P331	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.	
P302 + P352	IF ON SKIN: Wash with plenty water.	
P332 + P313	If skin irritation occurs: Get medical advice/attention.	
P362 + P364	Take off contaminated clothing and wash it before reuse.	
P304 + P340	P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P312	Call a POISON CENTER/doctor if you feel unwell.	
	Section continued on the next page	

Page **3** of **17** Date of Revision:08 February 2016 / Ver. 2.01



409B-AEROSOL

Continued...

Storage	Precautionary Statements
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
P403	Store in well-ventilated place.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents/container in accordance to local/regional/international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Composition/Information on Ingredients

CAS # Chemical Name		%(weight)
811-97-2	1,1,1,2-tetrafluoroethane	25%
107-83-5	methyl-2-pentane	30-38%
96-14-0	methyl-3-pentane	11-15%
79-29-8	dimethyl-2,3-butane	11-15%
75-83-2	dimethyl-2,2-butane	7-11%
109-66-0	pentane	4-8%
110-54-3	n-hexane	1-4%



409B-AEROSOL

Section 4: First-Aid Measures		
Exposure Condition	GHS Code/Symptoms/Precautionary Statements	
IF SWALLOWED	P301 + P310, P331, P308 + P313	
Immediate Symptoms	nausea, weakness, headache, abdominal pain, drowsiness, dizziness, unconsciousness	
Response	Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.	
	IF exposed or concerned: Get medical advice/attention.	
IF ON SKIN	P302 + P352, P332 + P313, P362 + P364, P308 + P313	
Immediate Symptoms	dry skin, redness, irritation	
Response	Wash with plenty of water.	
	If skin irritation occurs: Get medical advice/attention.	
	IF exposed or concerned: Get medical advice/attention.	
	Take off contaminated clothing and wash it before reuse.	
IF INHALED	P304 + P340, P312, P308 + P313	
Immediate Symptoms	nausea, weakness, headache, drowsiness, dizziness, unconsciousness	
Response	Remove person to fresh air and keep comfortable for breathing.	
	Call a POISON CENTER/doctor if you feel unwell.	
	IF exposed or concerned: Get medical advice/attention.	
IF IN EYES	P305 + P351 + P338, P308 + P313	
Immediate Symptoms	redness	
Response	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
	IF exposed or concerned: Get medical advice/attention.	



409B-AEROSOL

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
	Use water spray to cool containers.
Specific Hazards	Aerosols containers may erupt with force at temperatures above 50 °C [122 °F].
	Produces irritating and toxic fumes in fires or in contact with hot surfaces.
	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
	Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO, CO_2), halogenated compounds, and hydrogen fluorides.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Avoid breathing the mist/spray/vapors. Remove or keep away all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways.
Containment Methods	Not applicable
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose of spill waste according to Section 13.



409B-AEROSOL

Section	7: Handling and Storage	
---------	-------------------------	--

Prevention	Keep out of reach of children.
	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area.
	Do not pierce or burn, even after use.
Handling	Do not spray on an open flame or other ignition source.
	Use only outdoors or in a well-ventilated area.
	Wear protective gloves/protective clothing/eye protection.
	Wash hands thoroughly after handling.
	Avoid release to the environment.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50 °C [122 °F].
	Store in well ventilated place.
	Store locked up.

Section 8: Exposure Controls/Personal Protection

Substances with Occupational Exposure Limit Values

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
1,1,1,2-tetrafluoroethane	MG Chemicals a)	1 000 ppm	Not established
	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	Canada	Not established	Not established
methyl-2-pentane	ACGIH	500 ppm	1 000 ppm
Hexane isomers	U.S.A. OSHA PEL	(500 ppm) ^{b)}	(1 000 ppm) ^{b)}
(except n-Hexane)	Canada AB	500 ppm	1 000 ppm
-	Canada BC	200 ppm	Not established
	Canada ON	500 ppm	1 000 ppm
	Canada QC	500 ppm	1 000 ppm

Section continued on the next page

Page **7** of **17** Date of Revision:08 February 2016 / Ver. 2.01



ELECTROSOLVETM CONTACT CLEANER

409B-AEROSOL

Continued

Chemical Name	Country/ Provinces	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
methyl-3-pentane <i>Hexane isomers</i> (except n-Hexane)	ACGIH U.S.A. OSHA PEL Canada AB Canada BC	500 ppm (500 ppm) ^{b)} 500 ppm 200 ppm	1 000 ppm (1 000 ppm) ^{b)} 1 000 ppm Not established
	Canada ON	500 ppm	1 000 ppm
	Canada QC	500 ppm	1 000 ppm
dimethyl-2,3-butane <i>Hexane isomers</i> (except n-Hexane)	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	500 ppm (500 ppm) ^{b)} 500 ppm 200 ppm 500 ppm 500 ppm	1 000 ppm (1 000 ppm) ^{b)} 1 000 ppm Not established 1 000 ppm 1 000 ppm
dimethyl-2,2-butane <i>Hexane isomers</i> (except n-Hexane)	ACGIH U.S.A. OSHA PEL Canada AB Canada BC	500 ppm (500 ppm) ^{b)} 500 ppm 200 ppm	1 000 ppm (1 000 ppm) ^{b)} 1 000 ppm Not established
	Canada ON	500 ppm	1 000 ppm
	Canada QC	500 ppm	1 000 ppm
pentane	ACGIH	1000 ppm	Not established
	U.S.A. OSHA PEL	1000 ppm	Not established
	Canada AB	600 ppm	Not established
	Canada BC	600 ppm	Not established
	Canada ON	600 ppm	750 ppm
	Canada QC	120 ppm	Not established
n-hexane	ACGIH	50 ppm ^{c)}	Not established
	U.S.A. OSHA PEL	50 ppm	Not established
	Canada AB	50 ppm	Not established
	Canada BC	20 ppm ^{c)}	Not established
	Canada ON	50 ppm ^{c)}	Not established
	Canada QC	50 ppm	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS database² and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) MG Chemicals recommended limit corresponding to prevalent international threshold values

b) Value vacated (retracted) under court order, but still in effect in some states.

c) Skin – significant exposure through skin route



409B-AEROSOL

Engineering Controls

Ventilation	Keep airborne concentrations below the occupational exposure
	limits (OEL).

Personal Protective Equipment

Eye protection	Wear appropriate protective eyeglasses or chemical safety goggles.
	Recommendation: Ensure that glasses have side shields for lateral protection.
Skin Protection	For likely contacts, use of protective butyl rubber or other chemically resistant gloves.
	For incidental contacts, use nitrile or other chemically resistant gloves.
Respiratory Protection	For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges.
	Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.
	RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.



ELECTROSOLVETM CONTACT CLEANER

409B-AEROSOL

Section 9: Physical and Chemical Properties

Physical State	Liquid, in an aerosol format	Lower Flammability Limit	1%
Appearance	Colorless	Upper Flammability Limit	7%
Odor	Mild hydrocarbon	Vapor Pressure @20 °C	33 kPa [250 mmHg]
Odor Threshold	Not available	Vapor Density	2.98 (Air =1)
рН	Not available	Specific Gravity @15.5 °C	0.66
Freezing/Melting	Not	Solubility in	Immiscible
Point	available	Water	
Boiling Point	52 °C	Partition	Not
	[125 °F]	Coefficient	available
Flash Point ^{a)}	-29 °C	Auto-ignition	Not
	[-20 °F]	Temperature	available
Evaporation	0.8 (Ether = 1)	Decomposition	Not
Rate		Temperature	available
Flammability	Not	Viscosity	<20.5 mm ² /s
(solid, gas)	available	@40 °C	

a) Closed cup flash point

Section 10: Stability and Reactivity

Reactivity	Not available
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Temperatures above 50 °C [122 °F], open flames, and incompatible substances
Incompatibilities	Strong oxidizing agents, alkali or alkali earth metals, powdered aluminum, zinc, magnesium, and beryllium
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.



409B-AEROSOL

Section 11: Toxicological Information

Routes of Exposure

Eye Contact, Ingestion, Inhalation, and Skin Contact

Symptoms Summary

Eyes May cause redness.

Inhalation May cause nausea, weakness, headache, drowsiness, dizziness, unconsciousness

Ingestion May cause nausea, weakness, headache, abdominal pain, drowsiness, dizziness, unconsciousness (also see inhalation symptoms).

- **Skin** May cause dry skin, redness, and irritation.
- **Chronic** Prolonged or repeated exposure may cause skin dryness, cracking, as well as defatting the skin.

Ingestion or inhalation of paint material, mist, or vapor during pregnancy may increase the chances fetal death and developmental defects.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50	LD50	LC50
	oral	dermal	inhalation
1,1,1,2-tetrafluoroethane	Not	Not	1 500 g/m³
	available	available	4 h Rat
methyl-2-pentane	Not	Not	3 125 ppm
	available	available	4 h Rat ^{a)}
methyl-3-pentane	Not	Not	Not
	available	available	available
dimethyl-2,3-butane	Not	Not	Not
	available	available	available
dimethyl-2,2-butane	Not	Not	Not
	available	available	available
pentane	>2 000 mg/kg	Not	>20 mg/L
	Rat	available	Rat 4 h (vapor)
n-hexane	15 480 mg/kg	>1.3 g/kg	627 000 ppm
	Rat	Rabbit ^{a)}	3 min Rat

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier (M)SDS were also consulted.

a) Data from supplier (M)SDS



409B-AEROSOL

Other Toxicological Effects

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Based on available data, the classification criteria are not met.
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Based on available data, the classification criteria are not met.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	The n-hexane component was found to harm fetus in animal studies.
Teratogenicity (risk of fetus malformation)	Harm to fetus found in animal studies.
STOT-single exposure	The hexane isomers may affect the central nervous system.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Mixture is a class 1 aspiration hazard. It contain over 33% class 1 aspiration hazard components and has a mixture viscosity of <20.5 mm ² /s at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<u>http://echa.europa.eu</u>), and other reliable sources.

Similar mixtures of isoalkanes C6-C7 with <5% n-hexane have a LC50 of 11.4 mg/L for rainbow trout (Oncorhynchus mykiss) 96 h, and an EL50 of 3.0 mg/L water flea (Daphnia magna) 48 h.

Acute Ecotoxicity

Category 2 Toxic to aquatic life Avoid release to the environment.

Section continued on the next page

Page **12** of **17** Date of Revision:08 February 2016 / Ver. 2.01



409B-AEROSOL

Chronic Ecotoxicity

Category 3 Harmful to aquatic life with long lasting effects

Avoid release to the environment. Collect spillage.

Biodegradability

Not available

Other Effects

Actual VOC (Volatile Organic Compounds) content according to the US (EPA) and Canadian (CEPA) authorities.

Actual VOC = 75% [495 g/L]

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information

Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations); **USA CFR 49 Regulations** (Parts 100 to 185).

Limited Quantity



UN number: UN1950 Shipping Name: AEROSOL, flammable Class: 2.1 Packing Group: Not applicable Marine Pollutant: Yes



ELECTROSOLVETM CONTACT CLEANER

409B-AEROSOL

Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Limited Quantity See package instruction Y203




Max Net Qty/Pkg 30 kg G

UN number: UN1950 Shipping Name: AEROSOL, flammable **Class:** 2.1 Packing Group: Not applicable Marine Pollutant: Yes



Sea

Refer to IMDG regulations.



UN number: UN1950 Shipping Name: AEROSOL, flammable **Class:** 2.1 Packing Group: Not applicable Marine Pollutant: Yes

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information

Canada

Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL.

Industry and Science Canada

MG Labels products intended for the workplace to conform to WHMIS labeling regulations. Product identification, net quantity declaration, minimum printing type size heights, and packaging of this product are in compliance.

Health Canada

Products produced by MG Chemicals intended for retail display conform to the Canadian Consumer Labeling Regulations.

Section continued on the next page

Page **14** of **17** Date of Revision:08 February 2016 / Ver. 2.01



409B-AEROSOL

USA

Other Classifications

HMIS® RATING

HEALTH:	*	2
FLAMMABILITY:		3
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		

NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain products that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains n-hexane (CAS# 110-54-3) which has a 5,000 lb reporting quantity requirements in section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA).

This product does not contain any substances known to be listed in California.

Europe

RoHS (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.



409B-AEROSOL

Section 16: Other Information		
SDS Prepared by	Michel Hachey	
Date of Review	08 February 2016	

Supersedes09 May 2013Reason for Changes:Change in composition and reclassification in compliance with

HCS 2012 and WHMIS 2015 due to supplier revision.

Reference

1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

- ACGIH American Conference of Governmental Industrial Hygienists (USA)
- ECHA European Chemicals Agency
- EU European Union
- EC50 Half maximal effective concentration
- EL50 Half maximal effective loading
- IARC International Agency for Research on Cancer
- NOELR No observable effect loading ratio
- NTP National Toxicology Program
- GHS Globally Harmonized System of Classification of Labeling of Chemicals
- LC50 Lethal Concentration 50%
- LCLo Lowest published lethal concentration
- LD50 Lethal Dose 50%
- OEL Occupational Exposure Limit
- PEL Permissible Exposure Limit
- SDS Safety Data Sheet
- STEL Short-Term Exposure Limit
- TCLo Lowest published toxic concentration
- TWA Time Weighted Average
- VOC Volatile Organic Content



Burlington, Ontario, Canada

ELECTROSOLVETM CONTACT CLEANER

409B-AEROSOL

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at <u>www.mgchemicals.com</u>.

Email: support@mgchemicals.com

Mailing Addresses Manufacturing & Support 1210 Corporate Drive Burlington, Ontario, Canada L7L 5R6 Head Office 9347–193rd Street Surrey, British Columbia, Canada V4N 4E7

Disclaimer This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.