

Specifications

Units: Imperial Metric

| | |
|--|---------------------------------|
| Maximum Operating Pressure (psi) | 5,000 |
| Maximum Cylinder Capacity Advance (lbs) | 3900 |
| Maximum Cylinder Capacity Retract (lbs) | 2330 |
| Stroke (in) | 1.5 |
| Return Type | Double-Acting, Hydraulic Return |
| Plunger Type | Solid |
| Material | Steel |
| Cylinder Effective Area Advance (in ²) | 0.77 |
| Cylinder Effective Area Retract (in ²) | 0.46 |
| Oil Capacity Advance (in ³) | 1.18 |
| Oil Capacity Retract (in ³) | 0.7 |
| Weight (lbs) | 3.4 |

Dimensions

Units: Imperial Metric

| | |
|--------------------------|-------------|
| Dimension A (in) | 5.18 |
| Dimension B (in) | 3.68 |
| Dimension C (in) | 3.43 |
| Dimension C1 (in) | 0.63 |
| Dimension D (in) | 1.875-16 UN |
| Dimension D1 (in) | 1.73 |
| Dimension E (in) | 0.63 |
| Dimension E1 (in) | 0.59 |
| Dimension F (in) | 1.61 |
| Dimension K (in) | .313-24 UNF |
| Dimension L Retract (in) | 0.53 |
| Dimension M Extend (in) | 0.39 |
| Dimension P (in) | 0.26 |
| Dimension S (in) | 0.5 |
| Dimension T (in) | 0.47 |