

## Specifications

Units:	<b>Imperial</b>	Metric
Maximum Operating Pressure (psi)	5,000	
Maximum Cylinder Capacity Advance (lbs)	6110	
Maximum Cylinder Capacity Retract (lbs)	4080	
Stroke (in)	0.57	
Return Type	Double-Acting, Hydraulic Return	
Plunger Type	Solid	
Material	Steel	
Cylinder Effective Area Advance (in <sup>2</sup> )	1.22	
Cylinder Effective Area Retract (in <sup>2</sup> )	0.82	
Oil Capacity Advance (in <sup>3</sup> )	0.72	
Oil Capacity Retract (in <sup>3</sup> )	0.48	
Weight (lbs)	2.6	

## Dimensions

Units:	<b>Imperial</b>	Metric
Dimension A (in)	3.37	
Dimension B (in)	2.8	
Dimension C (in)	2.54	
Dimension C1 (in)	0.67	
Dimension D (in)	2.125-16 UN	
Dimension D1 (in)	2.02	
Dimension E (in)	0.71	
Dimension E1 (in)	0.67	
Dimension F (in)	1.87	
Dimension K (in)	.375-16 UNC	
Dimension L Retract (in)	0.65	
Dimension M Extend (in)	0.39	
Dimension P (in)	0.26	
Dimension S (in)	0.62	
Dimension T (in)	0.47	