

Specifications

Units:	Imperial	Metric
Maximum Operating Pressure (psi)	5,000	
Maximum Cylinder Capacity Advance (lbs)	3800	
Stroke (in)	0.98	
Return Type	Single-Acting, Spring Return	
Plunger Type	Solid	
Material	Steel	
Cylinder Effective Area Advance (in ²)	0.76	
Oil Capacity Advance (in ³)	0.75	
Piston (in)	0.98	
Rod (in)	0.63	
Weight (lbs)	4	

Dimensions

Units:	Imperial	Metric
Dimension A (in)	4.92	
Dimension B (in)	3.94	
Dimension C (in)	3.62	
Dimension D (in)	2.56	
Dimension F (in)	0.63	
Dimension F1 (in)	0.59	
Dimension G (in)	G1/8"	
Dimension H (in)	0.47	
Dimension J (in)	2.24	
Dimension K (in)	M8 x 1,25	
Dimension L (in)	1.97	
Dimension M (in)	1.18	
Dimension N (in)	0.3	
Dimension O (in)	0.49	
Dimension P (in)	1.77	
Dimension Q (in)	2.36	
Dimension R (in)	0.89	
Dimension S (in)	0.51	
Dimension T (in)	0.24	
Dimension U (in)	1.06	
Dimension V (in)	0.35	
Dimension W (in)	0.47	
Dimension X (in)	2.36	
Dimension Z (in)	0.05	