

Specifications

Units:

Imperial

Metric

Maximum Operating Pressure (psi)	5,000
Maximum Cylinder Capacity Advance (lbs)	9750
Stroke (in)	0.98
Return Type	Single-Acting, Spring Return
Plunger Type	Solid
Material	Steel
Cylinder Effective Area Advance (in ²)	1.95
Oil Capacity Advance (in ³)	1.92
Piston (in)	1.57
Rod (in)	0.98
Weight (lbs)	5.9

Dimensions

Units:

Imperial

Metric

Dimension A (in)	5.13
Dimension B (in)	4.15
Dimension C (in)	3.66
Dimension D (in)	3.15
Dimension F (in)	0.98
Dimension F1 (in)	0.94
Dimension G (in)	G1/8"
Dimension H (in)	0.36
Dimension J (in)	2.26
Dimension K (in)	M16 x 2,0
Dimension L (in)	2.36
Dimension M (in)	1.38
Dimension N (in)	0.39
Dimension O (in)	0.98
Dimension P (in)	2.17
Dimension Q (in)	2.46
Dimension R (in)	1.08
Dimension S (in)	0.87
Dimension T (in)	0.37
Dimension U (in)	1.07
Dimension V (in)	0.42
Dimension W (in)	0.39
Dimension X (in)	2.46
Dimension Z (in)	0.05