

## Specifications

Units:

**Imperial**

Metric

Maximum Operating Pressure (psi)	5,000
Maximum Cylinder Capacity Advance (lbs)	15200
Stroke (in)	0.98
Return Type	Single-Acting, Spring Return
Plunger Type	Solid
Material	Steel
Cylinder Effective Area Advance (in <sup>2</sup> )	3.04
Oil Capacity Advance (in <sup>3</sup> )	3
Piston (in)	1.97
Rod (in)	1.26
Weight (lbs)	9.7

## Dimensions

Units: **Imperial** Metric

Dimension A (in)	5.63
Dimension B (in)	4.65
Dimension C (in)	2.09
Dimension D (in)	3.94
Dimension F (in)	1.26
Dimension F1 (in)	1.22
Dimension G (in)	G1/4"
Dimension H (in)	0.54
Dimension J (in)	2.52
Dimension K (in)	M20 x 2,5
Dimension L (in)	3.15
Dimension M (in)	1.77
Dimension N (in)	0.41
Dimension O (in)	1.18
Dimension P (in)	2.6
Dimension Q (in)	2.63
Dimension R (in)	1.3
Dimension S (in)	1.06
Dimension T (in)	0.43
Dimension U (in)	1.15
Dimension V (in)	0.49
Dimension W (in)	0.6
Dimension X (in)	2.57
Dimension Z (in)	0.05