












Model	Description	Dimensions
 <p><b>Model# G5</b> <b>Order# 18905</b></p>	<ul style="list-style-type: none"> <li>▶ Liquid filled dampens needle vibration.</li> <li>▶ Reads both PSI and Bar</li> <li>▶ ±1.5% full scale accuracy.</li> <li>▶ 500 psi increment up to 10,000 PSI</li> <li>▶ Stainless steel casing.</li> </ul>	 <p>2.50" .56" Square 1/4" NPT</p>
 <p><b>Model# G6</b> <b>Order# 18906</b></p>	<ul style="list-style-type: none"> <li>▶ 10,000 psi to 15,000 psi warning zone.</li> <li>▶ The calibrated scale reads from 0-10,000 psi</li> <li>▶ Reads both PSI and Bar</li> <li>▶ Liquid filled dampens needle vibration.</li> <li>▶ ±1.5% full scale accuracy.</li> <li>▶ Large easy to read 4" face.</li> <li>▶ Rubber blowout plugs for safety.</li> <li>▶ Stainless steel casing.</li> </ul>	 <p>4.00" .78" Hex 1/4" NPT</p>
 <p><b>G7</b></p>	<ul style="list-style-type: none"> <li>▶ 10,000 psi to 15,000 psi warning zone.</li> <li>▶ The calibrated scale reads from 0-10,000 psi</li> <li>▶ Reads both PSI and Bar</li> <li>▶ Liquid filled dampens needle vibration.</li> <li>▶ ±2% full scale accuracy.</li> <li>▶ Large easy to read 4" face.</li> <li>▶ Standard on all Simplex Torque Wrench Pumps.</li> </ul>	 <p>4.00" 1/4" NPT</p>
 <p><b>GD1</b></p>	<ul style="list-style-type: none"> <li>▶ Designed for high cycle pressure applications</li> <li>▶ Self powered Lithium batteries.</li> <li>▶ Full 4 digit display.</li> <li>▶ + / - .25% full scale accuracy.</li> <li>▶ 10 million cycle life minimum.</li> <li>▶ Stainless steel sensor that is vibration &amp; shock resistant.</li> <li>▶ The calibrated scale reads from 0-10,000 psi</li> </ul>	 <p>2.66" .62" 1/4" NPT</p>
 <p><b>GD2</b></p>	<ul style="list-style-type: none"> <li>▶ .75" characters and 270° bar graph "analog" readout.</li> <li>▶ Splash proof phenolic housing.</li> <li>▶ + / - .25% full scale accuracy.</li> <li>▶ Keypad enable/disable of peak high or peak low hold.</li> <li>▶ Stainless steel sensor that is vibration &amp; shock resistant.</li> <li>▶ The calibrated scale reads from 0-10,000 psi</li> </ul>	 <p>5.45" 1.33" .87" Flats 1/4" NPT</p>

System Accessories

### SCALED TONNAGE GAUGES FOR SIMPLEX CYLINDERS

Model	Cylinder Tonnage	Face Diameter	Applicable Cylinder Series
 <p><b>GT5</b></p>	5, 10, 15	4"	R5, R10, R15, RFS10, RLS101, RDA1010
<b>GT20</b>	20, 50	4"	RLS201, RLS502, RLS1002, RFS20, RFS50, RFS100
<b>GT25</b>	25, 55, 100	4"	R25, R55, RDA55, R100
<b>GT30</b>	30, 50, 100	4"	R308, RLS302, RFS30, RLN30, RLN50, RLN100, RLR306, RLR50, RLR100
<b>GT100</b>	150, 200	4"	RDA100, RDA200, RFS150, RLN150, RLN200, RLR150, RLR200
<b>GT150</b>	100, 150, 200	4"	RDA150
<b>GTH12</b>	12, 20, 30	4"	RC12, RC20, RC30, RCD30
<b>GTH60</b>	60, 100, 150	4"	RC60, RC1003, RCD6010, RCD100, RCD1505