

Specifications

Units: Imperial Metric

| | |
|---|---------|
| Clamping Force (lbs) | 2700 |
| Stroke (in) | 1.17 |
| Mounting Thread J UNF | .312-24 |
| Manifold O-ring ARP No. or Inside Ø x thickness | -10 |
| Cylinder Effective Area (in ²) | 0.64 |
| Oil Capacity (in ³) | 0.77 |
| Standard Clamp Arm | LCAS122 |
| Weight (lbs) | 10 |

Dimensions

Units: Imperial Metric

| | |
|-----------------------|--------------|
| Dimension C1 (in) | 1.46 |
| Dimension C2 (in) | 1.95 |
| Dimension C3 (in) | 3.12 |
| Dimension D (in) | 3.125 - 16un |
| Dimension D1 (in) | 4.02 |
| Dimension D2 (in) | 3.46 |
| Dimension E (degrees) | 28.5 |
| Dimension F (in) | 0.03 |
| Dimension H (in) | 0.47 |
| Dimension J (in) | 2.8 |
| Dimension K (in) | 1.18 |
| Dimension N (in) | 1.48 |
| Dimension P (in) | 0.47 |
| Dimension R (in) | 1.73 |
| Dimension S (in) | 1.039 |
| Dimension U1 (in) | 3.46 |
| Dimension U2 (in) | 2.91 |
| Dimension V (in) | 0.32 |
| Dimension X (in) | 1.484 |
| Dimension Y (in) | 2.01 |