

Specifications

Units: Imperial Metric

| | |
|--------------------------------------------|----------------------------|
| Maximum Operating Pressure (psi) | 10,150 |
| Capacity Class (tonnage) | 55 |
| Capacity (imperial tons) | 55 |
| Stroke (in) | 5.91 |
| Collapsed Height A (in) | 12.05 |
| Extended Height B (in) | 17.95 |
| Return Type | Single-Acting, Load Return |
| Cylinder Effective Area (in ²) | 10.99 |
| Oil Capacity Required (in ³) | 64.88 |
| Weight (lbs) | 58 |

Dimensions

Units: Imperial Metric

| | |
|----------------------------------------------------|-------|
| Collapsed Height A (in) | 12.05 |
| Collapsed Height With Optional Tilt Saddle A1 (in) | 12.60 |
| Extended Height B (in) | 17.95 |
| Outside Diameter D (in) | 4.92 |
| Cylinder Bore Diameter E (in) | 3.74 |
| Plunger Diameter F (in) | 2.95 |
| Base to Advance Port H (in) | 0.98 |
| Saddle Protrusion from Plunger K (in) | 0.24 |
| Saddle Diameter L (in) | 1.97 |
| Optional Tilt Saddle Diameter L1 (in) | 2.80 |
| Saddle Height N (in) | 0.79 |

