

## Specifications

Units:  Imperial  Metric

Maximum Spread (in)	3.54
Power Source	Mechanical
Maximum Operating Torque (Ft.lbs)	89
Capacity (imperial tons)	12.3
Tip Clearance (in)	0
Usable on Flanges Specified to Accept the Following Bolt Sizes	M30, M33, M36, 1 1/8", 1 1/4", 1 3/8"
Weight (lbs)	44.0

## Dimensions

Units:  Imperial  Metric

Dimension A (in)	20.3
Dimension A1, Minimum Axial Tool Space (for installation) (in)	8.8
Dimension A2, Minimum Axial Tool Space (installed) (in)	10.2
Dimension B (in)	9.8
Dimension C, Maximum Flange Clearance (in)	2.4
Dimension D (in)	3.5
Dimension E (in)	19.0
Dimension F (in)	2.4
Dimension F, Minimum Flange Joint Thickness (in)	3.8
Dimension F, Maximum Flange Joint Thickness (in)	9.4
Dimension R, Minimum Radial Space (in)	9.4
Dimension V, Minimum Valve/Spacer Thickness (in)	0
Dimension V, Maximum Valve/Spacer Thickness (in)	2.4
Case Dimensions (in)	25.2 x 21.3 x 6.5

SG4TM  
SG6TM  
SG11TM

