

Specifications

Units:	Imperial	Metric
Maximum Operating Pressure (psi)	5,000	
Minimum Operating Pressure (psi)	500	
Clamping Force (lbs)	1250	
Stroke (in)	0.89	
Stroke Clamping (in)	0.39	
Mounting Style	Lower Flange	
Return Type	Double-Acting	
Rotation Direction	Left	
Mounting Thread J UNF	.250-28	
Manifold O-ring ARP No. or Inside Ø x thickness	568-011	
Cylinder Effective Area Clamp (in ²)	0.28	
Cylinder Effective Area Unclamp (in ²)	0.59	
Oil Capacity Clamp (in ³)	0.25	
Oil Capacity Unclamp (in ³)	0.52	
Maximum Oil Flow (in ³ /min)	25	
Standard Clamp Arm	CAS51	
Weight (lbs)	2.5	

Dimensions

Units:

Imperial

Metric

Dimension A (in)	5.33
Dimension C (in)	3.68
Dimension C1 (in)	4.57
Dimension D (in)	1.37
Dimension D1 (in)	2.13
Dimension D2 (in)	2.25
Dimension F (in)	0.63
Dimension G (in)	SAE #4
Dimension H (in)	0.55
Dimension K (in)	0.76
Dimension N (in)	0.75
Dimension P (in)	1.58
Dimension Q (in)	.312-18 UNC
Dimension S (in)	1.614
Dimension T (in)	1.89
Dimension U (in)	1.97
Dimension V (in)	0.27
Dimension X (in)	0.565
Dimension Y (in)	30 degrees
Dimension Z (in)	60 degrees