

Specifications

Units: **Imperial** Metric

Hole Shape	Oblong
Imperial Hole Size (in)	.50 x 375
Imperial Bolt Size (in)	7/16"
Metric Hole Size (mm)	12,7 x 19
Metric Bolt Size (mm)	M12
Mild A7 Maximum Allowable Material Thickness To Be Punched (in)	0.50
Boiler Plate Maximum Allowable Material Thickness To Be Punched (in)	0.50
Structura IA36 Maximum Allowable Material Thickness To Be Punched (in)	0.44
Struct Corten ASTMA242 Maximum Allowable Material Thickness To Be Punched (in)	0.44
Cold Rolled C1018 Maximum Allowable Material Thickness To Be Punched (in)	0.44
Hot Rolled C1050 Maximum Allowable Material Thickness To Be Punched (in)	0.38
Hot Rolled C1095 Maximum Allowable Material Thickness To Be Punched (in)	0.25
Hot Rolled C1095 Annealed Maximum Allowable Material Thickness To Be Punched (in)	0.31
Stainless Annealed Maximum Allowable Material Thickness To Be Punched (in)	0.38
Stainless 304 Hot Rolled Maximum Allowable Material Thickness To Be Punched (in)	0.38
Stainless 316 Cold Rolled Maximum Allowable Material Thickness To Be Punched (in)	0.38
Compatible Products	SP35, SP35S, SP35SP, MSP351, MSP351PE. STP35H. STP35A