

## Specifications

Units:  Imperial  Metric

Maximum Operating Pressure (bar)	350
Minimum Operating Pressure (bar)	35
Clamping Force (kN)	5,6
Stroke (mm)	22,6
Stroke Clamping (mm)	10
Mounting Style	Threaded Body
Return Type	Double-Acting
Cylinder Effective Area Clamp (cm <sup>2</sup> )	1,81
Cylinder Effective Area Unclamp (cm <sup>2</sup> )	3,81
Oil Capacity Clamp (cm <sup>3</sup> )	4,10
Oil Capacity Unclamp (cm <sup>3</sup> )	8,52
Maximum Oil Flow (l/min)	0,4
Standard Clamp Arm	CAS52
Mounting Flange	MF352
Flange Nut	FN352
Dimension A (mm)	135
Weight (kg)	1,1

## Dimensions

Units:  Imperial  Metric

Dimension B (mm)	69
Dimension C (mm)	27,4
Dimension C1 (mm)	50,1
Dimension C2 (mm)	24,9
Dimension D (mm)	M35 x 1,5
Dimension D1 (mm)	47,5
Dimension D2 (mm)	38
Dimension F (mm)	16
Dimension G (mm)	G1/8"
Dimension H (mm)	10
Dimension J1 (mm)	66
Dimension K (mm)	19
Dimension N (mm)	19,1
Dimension P (mm)	40
Dimension Q (mm)	M8 x 1,25
Dimension T (mm)	48
Dimension Y (mm)	25 degrees
Dimension Z (mm)	50 degrees