

Specifications

Units:

Imperial

Metric

Maximum Operating Pressure (bar)	350
Minimum Operating Pressure (bar)	35
Clamping Force (kN)	4,9
Stroke (mm)	22.6
Stroke Clamping (mm)	9,9
Mounting Style	Upper Flange
Return Type	Single-Acting
Cylinder Effective Area Clamp (cm ³)	1,81
Oil Capacity Clamp (cm ³)	4,10
Maximum Oil Flow (l/min)	0,4
Standard Clamp Arm	CAS52
Dimension A (mm)	135,3
Weight (kg)	1,1

Dimensions

Units:

Imperial

Metric

Dimension B (mm)	69,3
Dimension C (mm)	27,4
Dimension C1 (mm)	50,1
Dimension D (mm)	34,8
Dimension D1 (mm)	54,0
Dimension D2 (mm)	57,2
Dimension F (mm)	16,0
Dimension G (mm)	G1/8"
Dimension H (mm)	9,9
Dimension K (mm)	19,2
Dimension N (mm)	19,1
Dimension P (mm)	40,0
Dimension Q (mm)	M8 x 1,25
Dimension S (mm)	41,0
Dimension T (mm)	47,9
Dimension U (mm)	50,0
Dimension V (mm)	6,8
Dimension W (mm)	66,0
Dimension X (mm)	14,4
Dimension Y (mm)	30 degrees
Dimension Z (mm)	60 degrees