

## Specifications

Units:	<input type="radio"/> Imperial	<input checked="" type="radio"/> Metric
Maximum Operating Pressure (bar)	350	
Minimum Operating Pressure (bar)	35	
Clamping Force (kN)	17,4	
Stroke (mm)	29,5	
Stroke Clamping (mm)	14,0	
Mounting Style	Upper Flange	
Return Type	Single-Acting	
Cylinder Effective Area Clamp (cm <sup>3</sup> )	7,10	
Oil Capacity Clamp (cm <sup>3</sup> )	19,99	
Maximum Oil Flow (l/min)	2,3	
Standard Clamp Arm	CAS202	
Dimension A (mm)	167,0	
Weight (kg)	3,5	

## Dimensions

Units:	<input type="radio"/> Imperial	<input checked="" type="radio"/> Metric
Dimension B (mm)	88,1	
Dimension C (mm)	28,4	
Dimension C1 (mm)	58,0	
Dimension D (mm)	62,6	
Dimension D1 (mm)	85,0	
Dimension D2 (mm)	70,0	
Dimension F (mm)	32,0	
Dimension G (mm)	G1/4"	
Dimension H (mm)	13,0	
Dimension K (mm)	30,1	
Dimension M (mm)	23,2	
Dimension N (mm)	34,4	
Dimension P (mm)	55,2	
Dimension Q (mm)	M12 x 1,75	
Dimension R (mm)	26,0	
Dimension S (mm)	29,1	
Dimension T (mm)	70,2	
Dimension U (mm)	55,0	
Dimension V (mm)	8,5	
Dimension W (mm)	78,9	
Dimension X (mm)	35,1	