

Specifications

Units:	<input type="radio"/> Imperial	<input checked="" type="radio"/> Metric
Maximum Operating Pressure (bar)	350	
Minimum Operating Pressure (bar)	35	
Clamping Force (kN)	33,1	
Stroke (mm)	32,6	
Stroke Clamping (mm)	16,0	
Mounting Style	Upper Flange	
Return Type	Single-Acting	
Cylinder Effective Area Clamp (cm ³)	12,39	
Oil Capacity Clamp (cm ³)	37,20	
Maximum Oil Flow (l/min)	3,9	
Standard Clamp Arm	CAS352	
Dimension A (mm)	189,3	
Weight (kg)	5,5	

Dimensions

Units:	<input type="radio"/> Imperial	<input checked="" type="radio"/> Metric
Dimension B (mm)	100,7	
Dimension C (mm)	28,2	
Dimension C1 (mm)	60,7	
Dimension D (mm)	76,8	
Dimension D1 (mm)	100,0	
Dimension D2 (mm)	89,0	
Dimension F (mm)	38,0	
Dimension G (mm)	G1/4"	
Dimension H (mm)	13,0	
Dimension K (mm)	40,0	
Dimension M (mm)	27,4	
Dimension N (mm)	43,4	
Dimension P (mm)	67,9	
Dimension Q (mm)	M16 x 2	
Dimension R (mm)	26,0	
Dimension S (mm)	34,4	
Dimension T (mm)	82,9	
Dimension U (mm)	70,0	
Dimension V (mm)	10,8	
Dimension W (mm)	88,6	
Dimension X (mm)	41,6	