

Specifications

Units: **Imperial** Metric

| | |
|--|-----------|
| Maximum Operating Pressure (psi) | 5,000 |
| Minimum Operating Pressure (psi) | 700 |
| Mounting Style | Cartridge |
| Maximum Support Force (lbs) | 2,500 |
| Plunger Contact Spring Force Advance (lbs) | 3.4 |
| Plunger Contact Spring Force Retract (lbs) | 5.2 |
| Oil Capacity (in ³) | 0.06 |
| Maximum Oil Flow (in ³ /min) | 60 |
| Stroke (in) | 0.36 |
| Ventilation Below Force Required | Yes |
| Weight (lbs) | 2 |

Dimensions

Units: **Imperial** Metric

| | |
|---------------------------|-------------|
| Dimension A (in) | 4.03 |
| Dimension B (in) | 3.67 |
| Dimension C (in) | 3.23 |
| Dimension D (in) | M42 x 1,5 |
| Dimension D1 (in) | 2.25 |
| Dimension E (in) | 0.629 |
| Dimension F (in) | 0.49 |
| Dimension K (in) | M10 x 1,5 |
| Dimension L (in) | 0.18 |
| Dimension M (in) | 2 |
| Dimension N (in) | 0.73 |
| Dimension W (in) | 2.37 |
| Mounting Dimension A (in) | 2.26-2.28 |
| Mounting Dimension B (mm) | M42 x 1,5 |
| Mounting Dimension C (in) | 1.499-1.501 |
| Mounting Dimension D (in) | 1.67-1.69 |
| Mounting Dimension E (in) | .69-.75 |
| Mounting Dimension F (in) | 2.46 |