

## Specifications

Units:

**Imperial**

Metric

|  |                              |
|--|------------------------------|
| Maximum Operating Pressure (psi)                             | 10,000                       |
| Capacity (imperial tons)                                     | 4                            |
| Cutter Head Return Type                                      | Single-Acting, Spring Return |
| Length (in)  | 15                           |
| Replacement Blade Model Number                               | WCB750                       |
| Steel Wire Rope Hempcore Or IWRC Cutting Capacity (in)       | 0.63                         |
| Round Bar Copper Wire Or Bar Cutting Capacity (in)           | 0.63                         |
| Round Bar Aluminum Wire Or Bar Cutting Capacity (in)         | 0.63                         |
| Round Bar Soft Steel Bolts Cutting Capacity (in)             | 0.63                         |
| Round Bar Reinforcing Bar Cutting Capacity (in)              | 0.38                         |
| Wire Strand Bare Copper Wire Strands Cutting Capacity (in)   | 0.63                         |
| Wire Strand Bare Aluminum Wire Strands Cutting Capacity (in) | 0.63                         |
| Wire Strand ACSR Cutting Capacity (in)                       | 0.63                         |
| Wire Strand Guy Steel Wire Strands Cutting Capacity (in)     | 0.56                         |
| Cable Telephone Cable CPP Cutting Capacity (in)              | Will not cut                 |
| Cable Under ground Cable Power Cutting Capacity (in)         | Will not cut                 |
| Weight (lbs)   | 8                            |