

Specifications

Units: Imperial Metric

Cylinder Compatability	Single-acting
Reservoir Capacity (in ³)	277
Output Flow Rate (in ³ /min) 100 psi	700
Output Flow Rate (in ³ /min) 10000 psi	60
Duty Cycle	Intermittent
Valve Operation	Manual
Valve Model	VM32
Power Source	Electric
Sound Level (dBa)	85 - 90

Units: Imperial Metric

Maximum Operating Pressure (bar)	700
Cylinder Compatability	Single-acting
Reservoir Capacity (cm ³)	4000
Usable Oil Capacity (litres)	4,0
Output Flow Rate at 7 bar (l/min)	11,5
Output Flow Rate at 50 bar (l/min)	8,8
Output Flow Rate at 350 bar (l/min)	1,2
Output Flow Rate at 700 bar (l/min)	1,0
Motor Size (kW)	1,25
Duty Cycle	Intermittent
Valve Operation	Manual
Valve Model	VM32
Power Source	Electric
Sound Level (dBa)	85 - 90
Relief Valve Adjustment Range (bar)	140 - 700
Weight (kg)	27

Dimensions

Units: Imperial Metric

Dimension A (mm)	424
Dimension B (mm)	142
Dimension C (mm)	279
Dimension D (mm)	152