

## Specifications

---

Units:  Imperial  Metric

|   |                         |
|---|-------------------------|
| Maximum Operating Pressure (psi)                | 5,000                   |
| Pressure Rating (psi) 2nd Stage                 | 5,000                   |
| Cylinder Compatability                          | Single-acting           |
| Reservoir Capacity (in <sup>3</sup> )           | 462                     |
| Reservoir Capacity (gal)                        | 2                       |
| Usable Oil Capacity (gal)                       | 1.8                     |
| Maximum Flow at Rated Pressure                  | 40 in <sup>3</sup> /min |
| Output Flow Rate (in <sup>3</sup> /min) No Load | 200                     |
| Motor Size (hp)                                 | 0.75                    |
| Motor Hertz                                     | 50/60 Hz                |
| Motor Phases                                    | 1 Ph                    |
| Motor Voltage                                   | 208-240 V               |
| Valve Function                                  | Advance / Retract       |
| Valve Operation                                 | Solenoid                |
| Solenoid Valve Voltage                          | 24VDC                   |
| Valve Model                                     | VE32D                   |
| Power Source                                    | Electric                |
| Pump Control                                    | Pendant                 |
| Motor Electrical Specification                  | 230 V, 1 Ph, 50/60 Hz   |
| Sound Level (dBa)                               | 71 - 75                 |

## Dimensions

---

Units:  Imperial  Metric

|             |      |
|-------------|------|
| Height (in) | 20.4 |
| Length (in) | 19.3 |
| Width (in)  | 11   |