

Specifications

Units: **Imperial** Metric

| | |
|---|-------------------------|
| Maximum Operating Pressure (psi) | 5,000 |
| Pressure Rating (psi) 2nd Stage | 5,000 |
| Cylinder Compatability | Double-acting |
| Reservoir Capacity (in ³) | 462 |
| Reservoir Capacity (gal) | 2 |
| Usable Oil Capacity (gal) | 1.8 |
| Maximum Flow at Rated Pressure | 40 in ³ /min |
| Output Flow Rate (in ³ /min) No Load | 200 |
| Motor Size (hp) | 0.75 |
| Motor Hertz | 50/60 Hz |
| Motor Phases | 1 Ph |
| Motor Voltage | 115 V |
| Valve Function | Advance / Retract |
| Valve Operation | Solenoid |
| Solenoid Valve Voltage | 24VDC |
| Valve Model | VEW43 |
| Power Source | Electric |
| Pump Control | Pendant |
| Motor Electrical Specification | 115 V, 1 Ph, 50/60 Hz |
| Sound Level (dBa) | 71 - 75 |

Dimensions

Units: **Imperial** Metric

| | |
|-------------|------|
| Height (in) | 20.4 |
| Length (in) | 19.3 |
| Width (in) | 11 |