

Specification

Units:

Imperial

Metric

Maximum Operating Pressure (psi)	5,000
Maximum Cylinder Capacity Advance (lbs)	60850
Maximum Cylinder Capacity Retract (lbs)	36650
Stroke (in)	2.2
Return Type	Double-Acting, Hydraulic Return
Plunger Type	Solid
Material	Steel
Cylinder Effective Area Advance (in ²)	12.17
Cylinder Effective Area Retract (in ²)	7.33
Oil Capacity Advance (in ³)	26.83
Oil Capacity Retract (in ³)	16.18
Piston (in)	3.93
Rod (in)	2.48
Weight (lbs)	40.1

Dimensions

Units: **Imperial** Metric

Dimension A (in)	8.19
Dimension B (in)	5.98
Dimension C (in)	5.22
Dimension D (in)	6.69
Dimension F (in)	0.7
Dimension F1 (in)	2.44
Dimension G (in)	G1/4"
Dimension H (in)	0.7
Dimension J (in)	3.05
Dimension K (in)	M30 x 3,5
Dimension L (in)	5.31
Dimension M (in)	3.54
Dimension N (in)	0.69
Dimension O (in)	1.97
Dimension P (in)	4.92
Dimension Q (in)	3.16
Dimension R (in)	2.46
Dimension S (in)	1.97
Dimension T (in)	0.67
Dimension U (in)	1.48
Dimension V (in)	0.71
Dimension W (in)	0.71
Dimension X (in)	3.15
Dimension Z (in)	0.07