
Specifications

Units: Imperial Metric

| | |
|--|---------------------------------|
| Maximum Operating Pressure (bar) | 350 |
| Maximum Cylinder Capacity Advance (kN) | 17,2 |
| Maximum Cylinder Capacity Retract (kN) | 10,4 |
| Stroke (mm) | 25 |
| Return Type | Double-Acting, Hydraulic Return |
| Cylinder Effective Area Advance (cm ²) | 5,10 |
| Cylinder Effective Area Retract (cm ²) | 3,03 |
| Oil Capacity Advance (cm ³) | 12,47 |
| Oil Capacity Retract (cm ³) | 7,58 |
| Weight (kg) | 1,3 |

Dimensions

Units: Imperial Metric

| | |
|-----------------------|-----------|
| Dimension A (mm) | 107,0 |
| Retract Height B (mm) | 82,0 |
| Dimension C (mm) | 75,5 |
| Dimension C1 (mm) | 16,0 |
| Dimension D (mm) | M48 x 1,5 |
| Dimension D1 (mm) | 47,5 |
| Dimension E (mm) | 15,8 |
| Dimension E1 (in) | 15,0 |
| Dimension F (mm) | 41,0 |
| Dimension K (mm) | M8 x 1,25 |
| Dimension L (mm) | 12,8 |
| Dimension M (mm) | 12,8 |
| Dimension P (mm) | 6,5 |
| Dimension S (mm) | 12,7 |
| Dimension T (mm) | 12,0 |
