

Specifications

Units:

Imperial

Metric

Maximum Operating Pressure (psi)	10,150
Capacity Class (tonnage)	200
Maximum Cylinder Capacity Advance (tons)	223
Stroke (in)	9.84
Collapsed Height A (in)	18.03
Extended Height B (in)	27.87
Return Type	Single-Acting, Load Return
Plunger Type	Solid
Material	Steel
Cylinder Effective Area Advance (in ²)	43.95
Oil Capacity Advance (in ³)	432.55
Sideload Resistance of Maximum Capacity (percentage)	10%
Surface Treatment	Nitride
Coupler	CR400 Coupler
Weight (lbs)	331

Dimensions

Units:

Imperial

Metric

Collapsed Height A (in)	18.03
Collapsed Height With Optional Tilt Saddle A1 (in)	18.74
Optional Tilt Saddle Addition To Collapsed Height A1 (in)	0.71
Optional Tilt Saddle Diameter J1 (in)	4.96
Extended Height B (in)	27.87
Outside Diameter D (in)	9.84
Cylinder Bore Diameter E (in)	7.48
Plunger Diameter F (in)	5.51
Base to Advance Port H (in)	1.85
Saddle Diameter J1 (in)	4.45
Saddle Protrusion from Plunger K (in)	0.12
Saddle Maximum Tilt Angle Radius (degrees)	5
Base Mounting Holes Thread V	M12 x 1,75
Collar Thread Size W	M250 x 3
Collar Thread Length X (in)	2.48

