

# Ultra-High Pressure Hoses & Couplers

- **Hose Reel and Stand:** Stainless steel stand with 21,750 psi hoses from 98.42 up to 885.8 ft. lengths
- All hose reels are built up with multiple 98.42 ft. length hoses
- Wide offering of hoses and system components to complete your tensioning system
- Can be used for subsea fastening systems
- Hoses can be inter-connected in multi-tool set-ups using nipples, couplers, T-pieces and Y-Pipe assemblies

**HT,  
B  
Series**



Hose Length:  
**3.28 - 98.42 feet**

Hose Reel & Stand:  
**98.42 - 885.8 feet**

Maximum Operating Pressure:  
**21,750 psi (1500 bar)**

## 21,750 PSI HOSE REEL & STANDS

Model Number		Stainless Steel Hose Reels with Stand (Hose with female half BR150 and male half BH150 couplers)
HT15000RS		Reel & Stand Assembly, No Fitting
HT15000HRS		Hose Reel & Stand, No Hose
HT15100HRS		Hose Reel & Stand, with 100 ft. hose
HT15200HRS		Hose Reel & Stand, with 200 ft. hose
HT15300HRS		Hose Reel & Stand, with 300 ft. hose
HT15400HRS		Hose Reel & Stand, with 400 ft. hose
HT15500HRS		Hose Reel & Stand, with 500 ft. hose
HT15600HRS		Hose Reel & Stand, with 600 ft. hose
HT15700HRS		Hose Reel & Stand, with 700 ft. hose
HT15900HRS		Hose Reel & Stand, with 900 ft. hose

## 21,750 PSI HOSES

Model Number	Hoses	Hose End 1	Hose End 2	Length (ft)
HT1503		1/4 BSPM 120° Cone	1/4 BSPM 120° Cone	3.28
HT1510		1/4 BSPM 120° Cone	1/4 BSPM 120° Cone	9.84
HT15100		1/4 BSPM 120° Cone	1/4 BSPM 120° Cone	98.42
HT1503HR *		<b>BH150</b>	<b>BR150</b>	3.28
HT1506HR *		<b>BH150</b>	<b>BR150</b>	5.90
HT1510HR *		<b>BH150</b>	<b>BR150</b>	9.84
HT1520HR *		<b>BH150</b>	<b>BR150</b>	20
HT15100HR *		<b>BH150</b>	<b>BR150</b>	98.42
HT1503RR *		<b>BR150</b>	<b>BR150</b>	3.28
HT1506RR *		<b>BR150</b>	<b>BR150</b>	5.90
HT1510RR *		<b>BR150</b>	<b>BR150</b>	9.84
HT1520RR *		<b>BR150</b>	<b>BR150</b>	20

\* Includes dust caps

H = Male Nipple (BH150); R = Female Coupling (BR150)

## 21,750 PSI COUPLERS

Description (Includes dust caps)	Accessories	Complete Set	Female Half	Male Half
Quick Disconnect Coupler		<b>B150</b>	<b>BR150</b>	<b>BH150</b>
Quick Disconnect Coupler and Adaptor Kit		<b>BW150AW</b>	-	-
Quick Disconnect Blanking Coupler Set*		<b>B150B</b>	<b>BR150B</b>	<b>BH150B</b>

## 21,750 PSI T-PIECES

Model Number	shown HT15TPMMF	End 1	End 2	End 3
HT15TPMMF		1x BH150	1x BH150	1x BR150
HT15TPMMM		1x BH150	1x BH150	1x BH150

## 21,750 PSI Y-PIPE ASSEMBLIES

Model Number	shown HT1506YTPMMF	End 1 Hose	End 2 Hose	End 3 T-Pieces
HT1506YTPMMF		HT1506HR	HT1506HR	HT15TPMMF
HT1510YTPMMF		HT1510HR	HT1510HR	HT15TPMMF
HT1506YTPFMF		HT1506RR	HT1506RR	HT15TPMMM
HT1510YTPFMF		HT1510RR	HT1510RR	HT15TPMMM

Y-Pipe Assembly: 1+2 = Adaptor; 3 = Stainless Steel T with 1/4" BSPM;  
4 = Male Nipple (BH150); 5 = Female Coupling (BR150); 6 = Hose