

Hydraulic Sync-Grip Master Puller Sets

▼ Shown: **MPS14H**



MPS Series

Puller Capacity:
14 - 50 tons

Maximum Reach:
12.6 - 27.6 inches

Maximum Spread:
13.8 - 38.6 inches

Maximum Operating Pressure:
10,000 psi

- Sync Grip mechanism synchronizes movement of all jaws for simultaneous engagement
- Hydraulically applied pulling force increases pulling capacity reducing operator fatigue
- Standard jaws adjust to accommodate different reach requirements. Optional long jaw sets available for additional reach requirements
- Designed for applications including pulling, pushing and dismantling gears, bearings, bushings, etc.

i Dimensions
Dimensional information for all puller models is included in the dimensional overview table:

Page: 188

i Sets Include:¹⁾

¹⁾ Choose pump options below.

▼ DIMENSIONAL DATA

Puller Capacity (ton)	Model No. (Puller and Cylinder)	Stroke (in)	Dimensions (in)		Wt. (lbs)	Hydraulic Puller Sets					Long Jaw Sets Model No. ^{***}	Dimensions (in)	
			Max. Reach A	Max. Spread B						All Sets Include:		Max. Reach A	Max. Spread B
						Hand Pump	Air Pump	Electric Pump	Cordless Pump				
14	SGH14	1.0	12.60	13.78	55.1	MPS14H	MPS14A	MPS14E	MPS14C	*	SG1002K	15.75	15.94
24	SGH24	2.0	12.60	18.90	108.0	MPS24H	MPS24A	MPS24E	MPS24C	GA45GC & HC7206C	SG2002K	17.13	21.26
36	SGH36	2.5	16.14	25.59	165.3	MPS36H	MPS36A	MPS36E	MPS36C		SG3002K	20.67	28.35
50**	SGH64	3.0	27.56	38.58	363.7	MPS64H	MPS64A	MPS64E	MPS64C	SG6002K	33.46	42.52	

* 14-ton sets include an AR630 female coupler, GA45 gauge adaptor, and G2535L gauge.
 ** Puller capacity at 7,850 psi, maximum cylinder capacity @ 10,000 psi is 64.6 tons.
 *** Jaw sets include three jaws.

For 115 V application add "B" suffix
 For 230 V application add "E" suffix