

Specifications

Units:

Imperial

Metric

Maximum Operating Pressure (bar)	350
Maximum Cylinder Capacity Advance (kN)	13,3
Maximum Cylinder Capacity Retract (kN)	6,3
Stroke (mm)	22,6
Return Type	Double-Acting, Hydraulic Return
Cylinder Effective Area Advance (cm ²)	13,3
Cylinder Effective Area Retract (cm ²)	6,3
Oil Capacity Advance (cm ³)	8,69
Oil Capacity Retract (cm ³)	4,10
Mounting Style	Lower Flange
Weight (kg)	1,1

Dimensions

Units:

Imperial

Metric

Dimension A (mm)	128,8
Dimension B (mm)	106,2
Dimension C1 (mm)	24,9
Dimension D (mm)	34,8
Dimension D1 (mm)	54,1
Diameter D2 (mm)	57,2
Dimension E (mm)	16,0
Dimension E1 (in)	15,0
Dimension F (mm)	13,0
Dimension H (mm)	14,0
Dimension K (mm)	M8 x 1,25
Dimension N (mm)	19,1
Dimension P (mm)	5,8
Dimension S (mm)	41,0
Dimension T (mm)	15,7
Dimension U (mm)	50,0
Dimension V (mm)	6,9
Dimension W (mm)	66,0
Dimension X (mm)	14,4