

## Specifications

---

Units:  Imperial  Metric

Maximum Operating Pressure (psi)	10,000
Capacity Class (tonnage)	100
Maximum Cylinder Capacity Advance (tons)	110.9
Stroke (in)	3.94
Collapsed Height A (in)	13.62
Extended Height B (in)	17.57
Return Type	Single-Acting, Spring Return
Plunger Type	Solid
Material	Aluminum
Cylinder Effective Area Advance (in <sup>2</sup> )	22.19
Oil Capacity Advance (in <sup>3</sup> )	87.43
Surface Treatment	Anodized
Coupler	CR400 Coupler
Weight (lbs)	53.3

## Dimensions

---

Units:  Imperial  Metric

Collapsed Height A (in)	13.62
Optional Tilt Saddle Addition To Collapsed Height A1 (in)	0.75
Optional Tilt Saddle Diameter J1 (in)	3.82
Extended Height B (in)	17.57
Outside Diameter D (in)	7.09
Cylinder Bore Diameter E (in)	5.32
Plunger Diameter F (in)	4.33
Base to Advance Port H (in)	1.82
Saddle Diameter J1 (in)	3.7
Saddle Protrusion from Plunger K (in)	0.12
Saddle Maximum Tilt Angle Radius (degrees)	5
Lock Nut Height S (in)	2.95
Base Mounting Holes Thread V	M10

