

## Specifications

---

Units:  Imperial  Metric

Maximum Operating Pressure (psi)	10,000
Capacity Class (tonnage)	150
Maximum Cylinder Capacity Advance (tons)	175.9
Stroke (in)	7.87
Collapsed Height A (in)	18.62
Extended Height B (in)	26.49
Return Type	Single-Acting, Spring Return
Plunger Type	Solid
Material	Aluminum
Cylinder Effective Area Advance (in <sup>2</sup> )	35.18
Oil Capacity Advance (in <sup>3</sup> )	276.87
Surface Treatment	Anodized
Coupler	CR400 Coupler
Weight (lbs)	97.4

## Dimensions

---

Units:  Imperial  Metric

Collapsed Height A (in)	18.62
Optional Tilt Saddle Addition To Collapsed Height A1 (in)	0.71
Optional Tilt Saddle Diameter J1 (in)	4.96
Extended Height B (in)	26.49
Outside Diameter D (in)	9.06
Cylinder Bore Diameter E (in)	6.69
Plunger Diameter F (in)	5.51
Base to Advance Port H (in)	2.02
Saddle Diameter J1 (in)	4.45
Saddle Protrusion from Plunger K (in)	0.12
Saddle Maximum Tilt Angle Radius (degrees)	5
Lock Nut Height S (in)	3.15
Base Mounting Holes Thread V	M10

