

Specifications

Units: **Imperial** Metric

Maximum Operating Pressure (psi)	10,000
Capacity Class (tonnage)	20
Maximum Cylinder Capacity Advance (tons)	24.2
Stroke (in)	7.87
Collapsed Height A (in)	13.35
Extended Height B (in)	21.23
Return Type	Double-Acting, Hydraulic Return
Plunger Type	Solid
Material	Aluminum
Cylinder Effective Area Advance (in ²)	4.83
Cylinder Effective Area Retract (in ²)	2.88
Oil Capacity Advance (in ³)	38.01
Oil Capacity Retract (in ³)	22.66
Surface Treatment	Anodized
Coupler	CR400 Coupler
Weight (lbs)	20.3

Dimensions

Units: **Imperial** Metric

Collapsed Height A (in)	13.35
Optional Tilt Saddle Addition To Collapsed Height A1 (in)	0.39
Optional Tilt Saddle Diameter J1 (in)	1.65
Extended Height B (in)	21.23
Outside Diameter D (in)	4.45
Cylinder Bore Diameter E (in)	2.48
Plunger Diameter F (in)	1.58
Base to Advance Port H (in)	1.19
Top to Retract Port (in)	1.97
Saddle Diameter J1 (in)	1.22
Saddle Protrusion from Plunger K (in)	0.12
Saddle Maximum Tilt Angle Radius (degrees)	5
Base Mounting Holes Thread V	M6

