

## Specifications

---

Units: **Imperial** Metric

Maximum Operating Pressure (psi)	10,000
Capacity Class (tonnage)	30
Maximum Cylinder Capacity Advance (tons)	34.2
Stroke (in)	7.87
Collapsed Height A (in)	13.83
Extended Height B (in)	21.7
Return Type	Double-Acting, Hydraulic Return
Plunger Type	Solid
Material	Aluminum
Cylinder Effective Area Advance (in <sup>2</sup> )	6.85
Cylinder Effective Area Retract (in <sup>2</sup> )	3.8
Oil Capacity Advance (in <sup>3</sup> )	53.91
Oil Capacity Retract (in <sup>3</sup> )	29.91
Surface Treatment	Anodized
Coupler	CR400 Coupler
Weight (lbs)	24.9

## Dimensions

---

Units: **Imperial** Metric

Collapsed Height A (in)	13.83
Optional Tilt Saddle Addition To Collapsed Height A1 (in)	0.43
Optional Tilt Saddle Diameter J1 (in)	2.17
Extended Height B (in)	21.7
Outside Diameter D (in)	4.92
Cylinder Bore Diameter E (in)	2.95
Plunger Diameter F (in)	1.97
Base to Advance Port H (in)	1.19
Top to Retract Port (in)	2.17
Saddle Diameter J1 (in)	1.61
Saddle Protrusion from Plunger K (in)	0.12
Saddle Maximum Tilt Angle Radius (degrees)	5
Base Mounting Holes Thread V	M6

