

## Specifications

Maximum Operating Pressure (psi)	10,000
Capacity Class (tonnage)	20
Maximum Cylinder Capacity Advance (tons)	23.6
Stroke (in)	2
Collapsed Height A (in)	6.38
Extended Height B (in)	8.38
Return Type	Single-Acting, Spring Return
Plunger Type	Hollow
Material	Steel
Cylinder Effective Area Advance (in <sup>2</sup> )	4.72
Oil Capacity Advance (in <sup>3</sup> )	9.46
Surface Treatment	Paint
Coupler	CR400 Coupler
Weight (lbs)	17

## Dimensions

Collapsed Height A (in)	6.38
Extended Height B (in)	8.38
Outside Diameter D (in)	3.88
Cylinder Bore Diameter E (in)	2.88
Plunger Diameter F (in)	2.13
Base to Advance Port H (in)	0.75
Saddle Diameter J1 (in)	2.13
Saddle Protrusion from Plunger K (in)	0.27
Plunger Internal Thread O (in)	1 9/16" - 16 un
Plunger Thread Length P (in)	0.75
Base Mounting Holes Bolt Circle U (in)	3.25
Base Mounting Holes Thread V	3/8"-16 unc
Collar Thread Size W	2 7/8" - 12
Collar Thread W (in)	3 7/8" - 12 un
Collar Thread Length X (in)	1.5
Center Hole Diameter Y (in)	1.06
Base Mounting Holes Thread Depth Z (in)	0.37

