

## Specifications

Capacity Class (tonnage)	60
Maximum Cylinder Capacity Advance (tons)	63.6
Collapsed Height A (in)	9.75
Extended Height B (in)	12.75
Return Type	Single-Acting, Spring Return
Plunger Type	Hollow
Material	Steel
Cylinder Effective Area Advance (in <sup>2</sup> )	12.73
Oil Capacity Advance (in <sup>3</sup> )	38.2
Surface Treatment	Paint
Coupler	CR400 Coupler

## Dimensions

Collapsed Height A (in)	9.75
Extended Height B (in)	12.75
Outside Diameter D (in)	6.25
Cylinder Bore Diameter E (in)	4.88
Plunger Diameter F (in)	3.63
Base to Advance Port H (in)	1.25
Saddle Diameter J1 (in)	3.61
Saddle Protrusion from Plunger K (in)	0.5
Plunger Internal Thread O (in)	2 3/4" - 16 un
Plunger Thread Length P (in)	0.75
Base Mounting Holes Bolt Circle U (in)	5.13
Base Mounting Holes Thread V	1/2"-13 unc
Collar Thread Size W	6 1/4" - 12
Collar Thread W (in)	6 1/4" - 12
Collar Thread Length X (in)	1.91
Center Hole Diameter Y (in)	2.12
Base Mounting Holes Thread Depth Z (in)	0.55

