
▼ Shown cylinder-pump set: SCR1010H



- Optimum match of individual components
- All sets are ready to use and include single-acting cylinder, two-speed pump, 6-foot safety hose, calibrated gauge with gauge adaptor

# The Quickest and Easiest Way to Start Working Right Away





### LW16 Lifting Wedge

Hydraulic cylinders, jacks and lifting wedges can also be used to assist in positioning and aligning.

The LW16 only requires an access gap of 0.39 inch. See our "Specialty Tools" section on **www.enerpac.com**.

Page: 212

Cylinder Selection (See Cylinder Section of this catalog for full product descriptions)			Nominal Set Capacity	Cylinder Model No.	Stroke	Collapsed Height	
					(in)	(in)	
			5	RC55	5.00	8.50	
				RC102	2.13	4.78	
			10	RC106	6.13	9.75	
				RC1010	10.13	13.75	
	RC-Series, Single-Acting,		15	RC154	4.00	7.88	
				RC156	6.00	10.69	
			25	RC252	2.00	6.50	
	General Purpose Cylinders			RC254	4.00	8.50	
	For maximum versatility.			RC256	6.25	10.75	
	·			RC2514	14.25	18.75	
		6	50	RC506	6.25	11.13	
	RCS-Series, Single-Acting,		10	RCS101	1.50	3.47	
	Low-Height Cylinders		20	RCS201	1.75	3.88	
	Ideal where space is restricted.		30	RCS302	2.44	4.63	
	ideal where space is restricted.		50	RCS502	2.38	4.81	
		26	100	RCS1002	2.25	5.56	
	RCH-Series, Single-Acting, Hollow Cylinders For pushing and pulling applications.		12	RCH121	1.63	4.75	
			20	RCH202	2.00	6.31	
			30	RCH302	2.50	7.03	
	Tor pushing and pulling applications.		60	RCH603	3.00	9.75	
		34	100	RCH1003	3.00	10.00	

**62** www.enerpac.com

# **Single-Acting, Cylinder Pump Sets**

## **SELECTION EXAMPLE**

## Selected cylinder:

• RC106, Single-acting cylinder with 6.13" stroke

### Selected pump:

• P392, Lightweight hand pump

#### Set model number:

• SCR106H

#### Included:

- HC7206 hose
- GF10P gauge
- GA2 adaptor

#### **SET SELECTION:**

Select the cylinder

Select the pump

Find the set model number in the gray field of the matrix



# **GA45GC Gauge** Adaptor 3)

Protect yourself from system overloading by simply ordering one

part number for a pre-assembled gauge, adaptor block and coupler.

Page:

162

SC **Series** 



Capacity:

5 - 100 tons

1.50 - 14.25 inches

Maximum Operating Pressure:

10,000 psi



# **Hydraulic Tool Box**

Tool box with hand pump, gauge adaptor assembly, hose and RC-, RCS-, RSM-Series cylinder.

Page:

65

Pump sel	Pump selection (See Pump Section of this catalog for full product descriptions)					Accessories Included			
Hand Pump P142	Hand Pump P392	Hand Pump P80	Foot Pump P392FP	Air Pump Cordless Pum		Hose Model No.	Gauge Model No.	Gauge Adaptor Model No.	
			2	1	Mary Mary	-		i i	
SCR55H	_	_	-	_	_	HC7206	GP10S	GA4	
-	SCR102H	_	SCR102FP	SCR102XA	SCR102XCB	HC7206	GF10P	GA2	
-	SCR106H	_	SCR106FP	SCR106XA	SCR106XCB	HC7206	GF10P	GA2	
-	SCR1010H	_	SCR1010FP	SCR1010XA	SCR1010XCB	HC7206	GF10P	GA2	
-	SCR154H	-	SCR154FP	SCR154XA	SCR154XCB	HC7206	GP10S	GA2	
-	SCR156H	_	SCR156FP	SCR156XA	SCR156XCB	HC7206	GP10S	GA2	
-	SCR252H	-	SCR252FP	SCR252XA	SCR252XCB	HC7206	GF20P	GA2	
-	SCR254H	-	SCR254FP	SCR254XA	SCR254XCB	HC7206	GF20P	GA2	
-	SCR256H	_	-	SCR256XA	SCR256XCB	HC7206	GF20P	GA2	
-	-	SCR2514H	-	SCR2514XA <sup>1)</sup>	-	HC7206	GF20P	GA2	
_	_	SCR506H	_	SCR506XA <sup>1)</sup>	_	HC7206	GF50P	GA2	
_	SCL101H	-	SCL101FP	SCL101XA	_	HC7206	GF10P	GA2	
_	SCL201H	-	SCL201FP	SCL201XA	_	HC7206	GF230P	GA2	
_	SCL302H	-	SCL302FP	SCL302XA	SCL302XCB	HC7206	GF230P	GA2	
_	SCL502H	_	SCL502FP	SCL502XA	SCL502XCB	HC7206	GF510P	GA2	
_	_	SCL1002H	-	-	SCL1002XCB	HC7206	GF510P	GA2	
SCH121H	_	-	-	-	_	HB7206	GF120P	GA4	
-	SCH202H	-	SCH202FP	SCH202XA	SCH202XCB	HC7206	GF813P	GA3	
_	SCH302H	_	SCH302FP	SCH302XA	SCH302XCB	HC7206	GF813P	GA3	
-	-	SCH603H	-	SCH603XA <sup>1)</sup>	SCH603XCB	HC7206	GF813P	GA3	
_	_	SCH1003H	-	_	_	HC7206	GP10S	GA2	

<sup>1)</sup> With **XA12** air pump

<sup>&</sup>lt;sup>2)</sup> XC Cordless Pump includes 115 V charger, for 230 V charger replace the "B" in the model number with an "E".

<sup>&</sup>lt;sup>3)</sup> XC Pump Sets include only the HC7206 Hose and GA45GC Gauge Adaptor accessories