

Specifications

Units:

Imperial

Metric

Maximum Operating Pressure (bar)	350
Minimum Operating Pressure (bar)	35
Clamping Force (kN)	2,2
Stroke (mm)	16.5
Stroke Clamping (mm)	8
Mounting Style	Threaded Body
Return Type	Double-Acting
Cylinder Effective Area Clamp (cm ³)	0,77
Cylinder Effective Area Unclamp (cm ³)	1,55
Oil Capacity Clamp (cm ³)	1,31
Oil Capacity Unclamp (cm ³)	2,46
Maximum Oil Flow (l/min)	0,2
Standard Clamp Arm	CAS22
Mounting Flange	MF282
Flange Nut	FN282
Dimension A (mm)	112
Weight (kg)	0,5

Dimensions

Units:

Imperial

Metric

Dimension B (mm)	59
Dimension C (mm)	26,4
Dimension C1 (mm)	43,0
Dimension C2 (mm)	24,9
Dimension D (mm)	M28 x 1,5
Dimension D1 (mm)	39,4
Dimension D2 (mm)	33
Dimension F (mm)	10
Dimension G (mm)	G1/8"
Dimension H (mm)	10
Dimension J1 (mm)	53
Dimension K (mm)	16
Dimension N (mm)	15,5
Dimension P (mm)	24
Dimension Q (mm)	M6 x 1
Dimension T (mm)	31
Dimension Y (mm)	25 degrees
Dimension Z (mm)	50 degrees