

## Specifications

Units:

Imperial

**Metric**

Maximum Operating Pressure (bar)	350
Minimum Operating Pressure (bar)	35
Clamping Force (kN)	5,6
Stroke (mm)	22.6
Stroke Clamping (mm)	10
Mounting Style	Threaded Body
Return Type	Double-Acting
Cylinder Effective Area Clamp (cm <sup>3</sup> )	1,81
Cylinder Effective Area Unclamp (cm <sup>3</sup> )	3,81
Oil Capacity Clamp (cm <sup>3</sup> )	4,10
Oil Capacity Unclamp (cm <sup>3</sup> )	8,52
Maximum Oil Flow (l/min)	0,4
Standard Clamp Arm	CAS52
Mounting Flange	MF352
Flange Nut	FN352
Dimension A (mm)	135
Weight (kg)	1,1

## Dimensions

---

Units:	<input type="checkbox"/> Imperial	<input checked="" type="checkbox"/> Metric
Dimension B (mm)	69	
Dimension C (mm)	27,4	
Dimension C1 (mm)	50,1	
Dimension C2 (mm)	24,9	
Dimension D (mm)	M35 x 1,5	
Dimension D1 (mm)	47,5	
Dimension D2 (mm)	38	
Dimension F (mm)	16	
Dimension G (mm)	G1/8"	
Dimension H (mm)	10	
Dimension J1 (mm)	66	
Dimension K (mm)	19	
Dimension N (mm)	19,1	
Dimension P (mm)	40	
Dimension Q (mm)	M8 x 1,25	
Dimension T (mm)	48	
Dimension Y (mm)	25 degrees	
Dimension Z (mm)	50 degrees	

---