

Specifications

Units:

Imperial

Metric

| | |
|--|------------------------------|
| Maximum Operating Pressure (psi) | 10,000 |
| Capacity (imperial tons) | 13 |
| Cutter Head Return Type | Single-Acting, Spring Return |
| Oil Capacity (in ³) | 7.3 |
| Length (in) | 15 |
| Steel Wire Rope Hempcore Or IWRC Cutting Capacity (in) | 1.00 |
| Round Bar Copper Wire Or Bar Cutting Capacity (in) | 1.25 |
| Round Bar Aluminum Wire Or Bar Cutting Capacity (in) | 1.25 |
| Round Bar Soft Steel Bolts Cutting Capacity (in) | 0.88 |
| Round Bar Reinforcing Bar Cutting Capacity (in) | Will not cut |
| Wire Strand Bare Copper Wire Strands Cutting Capacity (in) | 2.00 |
| Wire Strand Bare Aluminum Wire Strands Cutting Capacity (in) | 2.00 |
| Wire Strand ACSR Cutting Capacity (in) | 2.00 |
| Wire Strand Guy Steel Wire Strands Cutting Capacity (in) | 0.75 |
| Cable Telephone Cable CPP Cutting Capacity (in) | Will not cut |
| Cable Under ground Cable Power Cutting Capacity (in) | 2.00 |
| Weight (lbs) | 23 |