

## Specifications

|                                  |                                 |        |
|----------------------------------|---------------------------------|--------|
| Units:                           | <b>Imperial</b>                 | Metric |
| Maximum Operating Pressure (psi) | 5,000                           |        |
| Minimum Operating Pressure (psi) | 725                             |        |
| Stroke (in)                      | 0.60                            |        |
| Return Type                      | Double-Acting, Hydraulic Return |        |
| Weight (lbs)                     | 7.5                             |        |

## Dimensions

|                   |                 |        |
|-------------------|-----------------|--------|
| Units:            | <b>Imperial</b> | Metric |
| Dimension A (in)  | 6.76            |        |
| Dimension B (in)  | 6.16            |        |
| Dimension C (in)  | 5.83            |        |
| Dimension C1 (in) | 0.71            |        |
| Dimension D (in)  | 2.750-16 un     |        |
| Dimension D1 (in) | 2.91            |        |
| Dimension E (in)  | 0.87            |        |
| Dimension E1 (in) | 0.79            |        |
| Dimension F (in)  | 2.17            |        |
| Dimension H1 (in) | 4.37            |        |
| Dimension K (in)  | .375-24 unf     |        |
| Dimension L (in)  | 0.79            |        |
| Dimension P (in)  | 0.20            |        |
| Dimension S (in)  | Ø.11            |        |