

## Specifications

Units:

**Imperial**

Metric

Maximum Operating Pressure (psi)	5,000
Pressure Rating (psi) 1st Stage	200
Pressure Rating (psi) 2nd Stage	5,000
Cylinder Compatability	Single-acting
Reservoir Capacity (in <sup>3</sup> )	231
Usable Oil Capacity (gal)	1
Maximum Flow at Rated Pressure	25 in <sup>3</sup> /min
Oil Flow Rate (in <sup>3</sup> /min) 1st Stage	200
Oil Flow Rate (in <sup>3</sup> /min) 2nd Stage	25
Motor Size (hp)	0.5
Motor Hertz	50/60 Hz
Motor Phases	1 Ph
Motor Voltage	115 V
Valve Function	Advance / Hold / Retract
Power Source	Electric
Pump Operation	Dump and Hold
Motor Electrical Specification	115 V, 1 Ph, 50/60 Hz
Current Draw (amps)	9.5
Sound Level (dBa)	85
Weight (lbs)	35

## Dimensions

Units:

**Imperial**

Metric

Dimension A (in)	14.5
Dimension B (in)	12.18
Dimension C (in)	14.72
Dimension D (in)	4.15
Dimension E (in)	5.12
Dimension F (in)	12.74
Dimension H (in)	0.4
Dimension J (in)	5.62