

## Specifications

---

Units:

**Imperial**

Metric

Maximum Operating Pressure (psi)	10,000
Cylinder Compatability	Double-acting
Reservoir Capacity (in <sup>3</sup> )	120
Usable Oil Capacity (in <sup>3</sup> )	120
Maximum Flow at Rated Pressure	15 in <sup>3</sup> /min
Output Flow Rate (in <sup>3</sup> /min) No Load	125
Output Flow Rate Load (in <sup>3</sup> /min)	15
Output Flow Rate (in <sup>3</sup> /min) 2000 psi	30
Number of Outlets	2
Motor Size (hp)	0.5
Duty Cycle	Intermittent
Valve Function	Advance / Neutral / Retract
Valve Operation	Manual
Valve Type	4-way, 3-position
Power Source	Battery
Charger Voltage (VAC)	115
Weight (lbs)	24.2

- ① Outlet "Advance" Port
- ② Oil Fill (*must use funnel*)
- ③ User Adjustable Relief Valve Access Port
- ④ Directional Control Valve \*
- ⑤ Shoulder Strap Connection Points
- ⑥ Safety Lock Feature \*
- ⑦ On/Off Switch \*
- ⑧ Inlet "Retract" Port  
(double-acting models only)

\* Single-acting and double-acting models only

**Dimensions shown in inches**

