

# Specification

Units:

**Imperial**

Metric

Maximum Operating Pressure (psi)	10,000
Cylinder Compatability	Single-acting
Reservoir Capacity (in <sup>3</sup> )	416
Usable Oil Capacity (gal)	2
Maximum Flow at Rated Pressure	60 in <sup>3</sup> /min
Output Flow Rate (in <sup>3</sup> /min) 100 psi	700
Output Flow Rate (in <sup>3</sup> /min) 700 psi	535
Output Flow Rate (in <sup>3</sup> /min) 5000 psi	76
Output Flow Rate (in <sup>3</sup> /min) 10000 psi	60
Motor Size (hp)	1.7
Motor Hertz	50/60 Hz
Motor Phases	1 Ph
Motor Voltage	115 V
Duty Cycle	Intermittent
Valve Operation	Manual
Valve Type	3-way, 3-position, Tandem Center, Venturi Return Assist Valve
Valve Model	VM33VAC
Power Source	Electric
Pump Control	Manual
Motor Electrical Specification	115 V, 1 Ph, 50/60 Hz
Relief Valve Adjustment Range (psi)	2,000 - 10,000
Weight (lbs)	63

# Dimensions

Units: **Imperial** Metric

Dimension A (in)	16.7
Dimension B (in)	5.6
Dimension C (in)	11
Dimension D (in)	8.1