

Specifications

Units:

Imperial

Metric

| | |
|---|-------------------------|
| Maximum Operating Pressure (psi) | 10,000 |
| Cylinder Compatability | Single-acting |
| Reservoir Capacity (in ³) | 277 |
| Usable Oil Capacity (gal) | 1 |
| Maximum Flow at Rated Pressure | 60 in ³ /min |
| Output Flow Rate (in ³ /min) 100 psi | 700 |
| Output Flow Rate (in ³ /min) 700 psi | 535 |
| Output Flow Rate (in ³ /min) 5000 psi | 76 |
| Output Flow Rate (in ³ /min) 10000 psi | 60 |
| Motor Size (hp) | 1.7 |
| Motor Hertz | 50/60 Hz |
| Motor Phases | 1 Ph |
| Motor Voltage | 115 V |
| Duty Cycle | Intermittent |
| Valve Function | Advance / Retract |
| Valve Operation | Manual |
| Valve Type | 3-way, 2-position |
| Valve Model | VM22 |
| Power Source | Electric |
| Pump Control | Manual |
| Motor Electrical Specification | 115 V, 1 Ph, 50/60 Hz |
| Sound Level (dBa) | 85 - 90 |
| Relief Valve Adjustment Range (psi) | 2,000 - 10,000 |
| Weight (lbs) | 56 |

Dimensions

Units:

Imperial

Metric

| | |
|------------------|------|
| Dimension A (in) | 16.7 |
| Dimension B (in) | 5.6 |
| Dimension C (in) | 11 |
| Dimension D (in) | 6 |

ZU-4 Series with 1 and 2 gallon reservoirs

