

Specifications

Units: **Imperial** Metric

Maximum Operating Pressure (psi)	10,000
Cylinder Compatability	Single-acting
Reservoir Capacity (in ³)	416
Usable Oil Capacity (gal)	2
Maximum Flow at Rated Pressure	60 in ³ /min
Output Flow Rate (in ³ /min) 100 psi	700
Output Flow Rate (in ³ /min) 700 psi	535
Output Flow Rate (in ³ /min) 5000 psi	76
Output Flow Rate (in ³ /min) 10000 psi	60
Motor Size (hp)	1.7
Motor Hertz	50/60 Hz
Motor Phases	1 Ph
Motor Voltage	115 V
Duty Cycle	Intermittent
Valve Function	Advance / Retract
Valve Operation	Manual
Valve Type	3-way, 2-position
Valve Model	VM22
Power Source	Electric
Pump Control	Manual
Motor Electrical Specification	115 V, 1 Ph, 50/60 Hz
Sound Level (dBA)	85 - 90
Relief Valve Adjustment Range (psi)	2,000 - 10,000
Weight (lbs)	66

Dimensions

Units: **Imperial** Metric

Dimension A (in)	16.7
Dimension B (in)	5.6
Dimension C (in)	11
Dimension D (in)	8.1

ZU-4 Series with 1 and 2 gallon reservoirs

