

PowerLite[®] 535W WXGA 3LCD Projector

Widescreen
Ultra Bright
3400 Lumens²
Color Brightness



The ultra bright, widescreen short-throw projector for reliable performance.

3x Brighter Colors¹, and reliable performance — 3LCD, 3-chip technology

One measurement of brightness is not enough — look for both high color brightness and high white brightness. The PowerLite 535W has:

Color Brightness: 3400 lumens²
White Brightness: 3400 lumens²

Giant, widescreen images — native WXGA resolution and 16:10 format

Large, engaging presentations, even in small spaces — short throw distance saves space; project a 116" image from just 4' away with minimal shadows and glare

Long-lasting, low-cost lamps — up to 10,000 hours in ECO Mode³

Flexible placement — install using a wall mount (optional) or place on a tabletop or cart

Convenient collaboration for BYOD classrooms — wirelessly share⁴ and compare students' work from multiple devices, simultaneously, with Moderator device management software⁵

Wireless projection from an array of devices — project from iPhone[®], iPad[®], Android[™] tablets and smartphones with the free Epson iProjection[™] App⁴ (wireless module sold separately)

Manage projectors and present remotely — easy network connectivity; software included

Powerful sound to engage every student — includes a built-in 16 W speaker and microphone input; or, use external speakers, even in Standby Mode



Specifications

Projection System 3LCD, 3-chip technology
Projection Method Front/rear/ceiling mount
Driving Method Poly-silicon TFT Active Matrix
Pixel Number 1,024,000 dots (1280 x 800) x 3
Color Brightness² Color Light Output: 3400 lumens
White Brightness² White Light Output: 3400 lumens
Aspect Ratio 16:10
Native Resolution 1280 x 800 (WXGA)
Resize 640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (SXGA), 1280 x 960 (SXGA2), 1280 x 1024 (SXGA3), 1360 x 768 (WXGA 60-2), 1440 x 900 (WXGA+), 1400 x 1050 (SXGA+), 1600 x 1200 (UXGA)
Lamp Type 215 W UHE
Lamp Life³
 Up to 10,000 hours (ECO Mode)
 Up to 5000 hours (Normal Mode)
Throw Ratio Range 0.48 – 0.65
Size (projected distance) 53" to 116" (1.35 to 2.95 m)
Keystone Correction Manual Vertical ± 15 degrees
Keystone Correction Manual Horizontal ± 15 degrees
Mac[®] Connectivity Projector is Mac compatible via USB, DVI to HDMI[®] or VGA adapter (not included)
Contrast Ratio Up to 16,000:1
Color Reproduction Up to 1.07 billion colors

Projection Lens

Type No optical zoom/Manual focus
F-number 1.60
Focal Length 6.4 mm
Zoom Ratio Digital zoom 1.0 – 1.35

Other

Display Performance NTSC: 480 lines, PAL: 576 lines (Depends on observation of the multi-burst pattern)
Input Signal NTSC/NTSC4.43/PAL/M-PAL/N-PAL/PAL60/SECAM
Speaker 16 W (mono)
Operating Temperature 41 ° to 95 °F (5 ° to 35 °C)
Power Supply Voltage 100 – 240 V ± 10%, 50/60 Hz
Power Consumption
 315 W (Normal Mode)
 230 W (ECO Mode)
 1.9 W Standby (Communication On)
 0.22 W Standby (Communication Off)
Fan Noise
 37 dB (Normal Mode)
 29 dB (ECO Mode)
Security Kensington[®] Security lock port, padlock and security cable hole, password protect function

Interfaces

Computer/component video: D-sub 15 pin x 2
 S-video: Mini DIN x 1
 Composite video: RCA (Yellow) x 1
 Audio in: RCA x 1 (L and R), Mini stereo x 2
 USB (Type B) connector x 1 (USB display, audio and mouse control)
 USB (Type A) connector x 1 (USB memory/document camera)
 HDMI x 1
 RJ-45 x 1
 Serial: RS-232c x 1
 Monitor out: D-sub 15 pin x 1
 Audio out: Mini stereo x 1
 Microphone: Mini stereo x 1
 Wireless LAN port: 802.11 b/g/n (optional – module sold separately)

Dimensions (W x D x H)

Including feet: 13.5" x 12.7" x 5.2"
Excluding feet: 13.5" x 12.7" x 3.7"
Weight 8.2 lb

Remote Control

Features Source search, video, LAN, computer, USB, power, aspect, color mode, volume, e-zoom, A/V Mute, freeze, menu, page up and down, help, auto, mouse functions, user, esc
Operating Angle
 Right/left: ± 30 degrees
 Upper/lower: 10 to ± 60 degrees
Operating Distance 19.7 ft (6 m)

Eco Features

RoHS compliant
 Recyclable product⁶
 Epson America, Inc. is a SmartWaySM Transport Partner⁷

Support

The Epson ConnectionSM
 Pre-sales support U.S. and Canada 800-463-7766
 Internet website www.epson.com

Service Programs

Two-year projector limited warranty, Epson[®] Road Service program, PrivateLine[®] dedicated toll-free support and 90-day limited lamp warranty

What's in the Box

PowerLite 535W projector, power cord, computer cable (VGA), projector remote control, batteries, user manual CD, projector software CD, Quick Setup Sheet, password protection sticker and lens cover



Ordering Information

PowerLite 535W	V11H671020
Genuine Epson lamp	V13H010L87
Replacement air filter	V13H134A47
Short-throw wall mount (ELPMB45)	V12H706020
PowerLite [®] Pilot [™] 2 (ELPCB02)	V12H614020
Active speakers (ELPSP02)	V12H467020
Wireless 802.11 b/g/n LAN unit (ELPAP07)	V12H418P12
Quick wireless connection USB key (ELPAP07)	V12H005M09
Epson DC-06 document camera	V12H321005
Epson DC-11 document camera	V12H377020
Epson DC-12 document camera	V12H594020
Epson DC-20 document camera	V12H500020
Universal projector ceiling mount	ELPMBPJF
Adjustable suspended ceiling channel kit	ELPMBP01
False ceiling plate kit	ELPMBP02
Structural round ceiling plate	ELPMBP03
Adjustable extension column (pipe) 8"-11"	ELPMB0C1
Duet [™] screen	ELPSC80
ES3000 portable screen (ELPSC26H)	V12H002S3Y



205 Westwood Ave, Long Branch, NJ 07740
 Phone: 866-94 BOARDS (26273) / (732)-222-1511
 Fax: (732)-222-7088 | E-mail: sales@touchboards.com

¹ Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Color brightness (color light output) measured in accordance with IDMS 15.4. Color brightness will vary depending on usage conditions. | ² Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | ³ Lamp life will vary depending upon mode selected, environmental conditions and usage. Lamp brightness decreases over time. | ⁴ Check your owner's manual to determine if a wireless LAN module must be purchased separately to enable wireless connection on your Epson projector. Epson projectors can be networked either through the Ethernet port on the projector (check model specifications for availability) or via a wireless connection. Not all Epson projectors are able to be networked. Availability varies depending on model. | ⁵ Moderator feature is part of EasyMP[®] Multi-PC Projection software. | ⁶ For convenient and reasonable recycling options, visit www.epson.com/recycle | ⁷ SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

Better Products for a Better Future[™]
eco.epson.com



Epson America, Inc.
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON, EasyMP and PowerLite are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future and Epson iProjection are trademarks of Seiko Epson Corporation. PrivateLine is a registered trademark, Duet and Pilot are trademarks and Epson Connection is a service mark of Epson America, Inc. iPad, iPhone and Mac are trademarks of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. SmartWay is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2014 Epson America, Inc. Com-SS-Oct-14 CPD-42062R1 10/14